

WBAZ

Stainless washer with sealing gasket

A2 stainless steel with EPDM gasket




WATERPROOF

Perfect watertight closure and excellent sealing thanks to the EPDM sealing gasket



RESISTANT TO UV RAYS

Excellent resistance to UV rays



DIRECT FASTENING ON SHEET METAL


Direct fastening on sheet metal when paired with hexagonal head Ø6.3-6.5 screws in galvanized or stainless steel. Ideal for use with TBS type Ø6 screws, which can be installed on sheet metal up to 0.7mm thick without pre-bored holes

TBS Ø6 AND VERSATILITY

Compatible with TBS type Ø6 screws, also overlapping on sheet metal caps. Ideal for various applications thanks to the adaptability of the EPDM gasket and the force of the stainless steel A2 washer



Codes and dimensions




WBAZ

screw [mm]	code	D [mm]	H [mm]	d [mm]	pcs/pkg
6,3 - 6,5	WBAZ25A2	25	15	6,5	100

WBAZ available in other colours upon request


Range of sheet-metal caps available upon request




Large-head carbon-steel TBS screw with white zinc coating for WBAZ

screw [mm]	code	L [mm]	b [mm]	d _k [mm]	pcs/pkg
TBS 6 TX30	TBS680	80	50	15,5	50
	TBS6100	100	60		
	TBS6120	120	75		
	TBS6140	140	75		
	TBS6160	160	75		
	TBS6180	180	75		
	TBS6200	200	75		
	TBS6220	220	100		
	TBS6240	240	100		
	TBS6260	260	100		
	TBS6280	280	100		
	TBS6300	300	100		


Installation




Correct tightening



Excessive tightening



Insufficient tightening



Tightening off axis

The thickness of the washer after installation is approximately $8 \div 9$ mm.