

FIRE STRIPE



INTUMESCENT THERMO-INFLATABLE FLEXIBLE GASKET

INTUMESCENT

It expands under the effect of strong heat. As it expands, it seals the cavity in which it is placed, blocking the passage of flames.

FIRE PROTECTION

Installable in tight spaces, it is perfect for the fire protection of our concealed fastening systems.



TECHNICAL DATA

Properties	standard	value	USC conversion
Colour	-	grey	-
Reaction to fire	EN 13501-1	B-s3, d0	-
	NF P92-501	M1 - non-flammable	-
Application temperature	-	+5 / +35 °C	+41 / +95 °F
Storage temperature	-	+1 / +25 °C	+33.8 / +77 °F
French VOC classification	ISO 16000	A+	-

⁽¹⁾ Store the product in a cool, dry place for no more than 12 months.

Waste classification (2014/955/EU): 08 04 10.

CODES AND DIMENSIONS

CODE	B	s	L	B	s	L	
	[mm]	[mm]	[m]	[in]	[mil]	[ft]	
FIRESTRIFE10	10	2	6	0.4	79	20	56



DURABILITY

The profile has good resistance to UV and thermal stress and is not subject to rotting.

FAST INSTALLATION

The tape is adhesive, is installed quickly and no support tools are required.