

## BARRA FILETTATA CLASSE ACCIAIO 5.8 E 8.8 PER ANCORANTI CHIMICI

- Completa di dado (ISO4032) e rondella (ISO7089)
- Acciaio 5.8 e 8.8 con zincatura galvanica bianca



### CODICI E DIMENSIONI

#### BARRA FILETTATA CLASSE ACCIAIO 5.8

| CODICE     |     | d<br>[mm] | L <sub>t</sub><br>[mm] | d <sub>0</sub><br>[mm] | d <sub>f</sub><br>[mm] | pz. |
|------------|-----|-----------|------------------------|------------------------|------------------------|-----|
| INA588110  |     | M8        | 110                    | 10                     | ≤ 9                    | 10  |
| INA5810105 | NEW | M10       | 105                    | 12                     | ≤ 12                   | 10  |
| INA5810140 | NEW |           | 140                    | 12                     | ≤ 12                   | 10  |
| INA5812140 | NEW | M12       | 140                    | 14                     | ≤ 14                   | 10  |
| INA5812195 | NEW |           | 195                    | 14                     | ≤ 14                   | 10  |
| INA5816160 |     | M16       | 160                    | 18                     | ≤ 18                   | 10  |
| INA5816195 | NEW |           | 195                    | 18                     | ≤ 18                   | 10  |
| INA5816245 | NEW |           | 245                    | 18                     | ≤ 18                   | 10  |
| INA5820245 | NEW | M20       | 245                    | 24                     | ≤ 22                   | 10  |
| INA5820330 | NEW |           | 330                    | 24                     | ≤ 22                   | 10  |
| INA5824330 | NEW | M24       | 330                    | 28                     | ≤ 26                   | 10  |
| INA5827330 | NEW | M27       | 330                    | 32                     | ≤ 30                   | 10  |

d<sub>0</sub> = diametro foro nel supporto / d<sub>f</sub> = diametro foro nell'elemento da fissare

#### BARRA FILETTATA CLASSE ACCIAIO 8.8

| CODICE     |     | d<br>[mm] | L <sub>t</sub><br>[mm] | d <sub>0</sub><br>[mm] | d <sub>f</sub><br>[mm] | pz. |
|------------|-----|-----------|------------------------|------------------------|------------------------|-----|
| INA8812140 | NEW | M12       | 140                    | 14                     | ≤ 14                   | 10  |
| INA8812195 | NEW |           | 195                    | 14                     | ≤ 14                   | 10  |
| INA8812245 | NEW |           | 245                    | 14                     | ≤ 14                   | 10  |
| INA8816160 | NEW | M16       | 160                    | 18                     | ≤ 18                   | 10  |
| INA8816195 | NEW |           | 195                    | 18                     | ≤ 18                   | 10  |
| INA8816245 | NEW |           | 245                    | 18                     | ≤ 18                   | 10  |
| INA8816330 | NEW |           | 330                    | 18                     | ≤ 18                   | 10  |
| INA8820245 | NEW | M20       | 245                    | 24                     | ≤ 22                   | 10  |
| INA8820330 | NEW |           | 330                    | 24                     | ≤ 22                   | 10  |
| INA8820495 | NEW |           | 495                    | 24                     | ≤ 22                   | 10  |
| INA8824330 | NEW | M24       | 330                    | 28                     | ≤ 26                   | 10  |
| INA8824495 | NEW |           | 495                    | 28                     | ≤ 26                   | 10  |
| INA8827330 | NEW | M27       | 330                    | 32                     | ≤ 30                   | 10  |
| INA8827495 | NEW |           | 495                    | 32                     | ≤ 30                   | 10  |

d<sub>0</sub> = diametro foro nel supporto / d<sub>f</sub> = diametro foro nell'elemento da fissare

### MONTAGGIO

