

BARRA ROSCADA CLASE ACERO 5.8 Y 8.8 PARA ANCLAJES QUÍMICOS

- Con tuerca (ISO4032) y arandela (ISO7089)
- Acero 5.8 y 8.8 con zincado galvanizado blanco



CÓDIGOS Y DIMENSIONES

BARRA ROSCADA CLASE ACERO 5.8

CÓDIGO		d [mm]	L _t [mm]	d ₀ [mm]	d _f [mm]	unid.
INA588110		M8	110	10	≤ 9	10
INA5810105	NEW	M10	105	12	≤ 12	10
INA5810140	NEW		140	12	≤ 12	10
INA5812140	NEW	M12	140	14	≤ 14	10
INA5812195	NEW		195	14	≤ 14	10
INA5816160		M16	160	18	≤ 18	10
INA5816195	NEW		195	18	≤ 18	10
INA5816245	NEW		245	18	≤ 18	10
INA5820245	NEW	M20	245	24	≤ 22	10
INA5820330	NEW		330	24	≤ 22	10
INA5824330	NEW	M24	330	28	≤ 26	10
INA5827330	NEW	M27	330	32	≤ 30	10

d₀ = diámetro agujero en el soporte / d_f = diámetro agujero en el elemento a fijar

BARRA ROSCADA CLASE ACERO 8.8

CÓDIGO		d [mm]	L _t [mm]	d ₀ [mm]	d _f [mm]	unid.
INA8812140	NEW	M12	140	14	≤ 14	10
INA8812195	NEW		195	14	≤ 14	10
INA8812245	NEW		245	14	≤ 14	10
INA8816160	NEW	M16	160	18	≤ 18	10
INA8816195	NEW		195	18	≤ 18	10
INA8816245	NEW		245	18	≤ 18	10
INA8816330	NEW		330	18	≤ 18	10
INA8820245	NEW	M20	245	24	≤ 22	10
INA8820330	NEW		330	24	≤ 22	10
INA8820495	NEW		495	24	≤ 22	10
INA8824330	NEW	M24	330	28	≤ 26	10
INA8824495	NEW		495	28	≤ 26	10
INA8827330	NEW	M27	330	32	≤ 30	10
INA8827495	NEW		495	32	≤ 30	10

d₀ = diámetro agujero en el soporte / d_f = diámetro agujero en el elemento a fijar

MONTAJE

