

HSS CUTTER

FOR CUTTING VENTILATION DUCTS IN TRUSSES

UNIVERSAL

It conveniently cuts all insulation materials and timber from trusses or walls.

FREEHAND USE

With a powerful hand drill, the hole cutter can be used freehand without additional tools. Approx. 500 rpm

CODES AND DIMENSIONS

CODE	Ø cutter [mm]	TL [mm]	EL [mm]	pcs
F2170086	85	420	300	1
F2170111	110	420	300	1
F2170130	130	420	300	1
F2170152	152	420	300	1
F2170170	170	420	300	1
F2170200	200	420	300	1

The supply includes: hexagonal connection (F2170005). Guide pin and drilling head must be ordered separately.

ADDITIONAL PRODUCTS - ACCESSORIES

CODE	description	A Ø [mm]	TL [mm]	EL [mm]	pcs
F2170030	guide pin with drilling head	20	470	410	1
F2170010	guide pin only	19,5	430	380	1
F3690002	drilling head only	8 - 20	70	40	1
F2170005	hexagonal connection for HSS SW 12 hole cutter				1



F2170010

F3690002



F2170005



MATERIAL

Bimetal HHS M42, 8% Co.

FIELDS OF USE

Cuts insulation material of any kind (glass and rock wool, polystyrene, wood fibre, etc.) as well as timber, chipboard and plasterboard panels. Cutting solid timber up to a thickness of 30 mm.