

Specifications:

Spec. n.	Description	Unit of measurement	Price per unit	Total price
1	HEAVY METAL ANCHORS: Supply and installation, as provided for in the technical drawings of the project, of fully threaded heavy metal anchors, with diameter $\varnothing = \dots$ mm length $L = \dots$ mm and nut diameter $\varnothing = \dots$ mm, HEAVY METAL ANCHORS marketed by Rotho Blaas srl (www.rothoblaas.com), having the following characteristics: - class 5.8 steel with $f_{u,k} \geq 500$ N/mm² - galvanic zinc coating - cold moulded, especially strong and resistant - ETA option 7 for applications on non-cracked concrete - CE marking for construction products in accordance with Directive 89/106/CEE in compliance with ETAG 001 guidelines Furthermore, the anchors are to be in possession of a conical expansion body with a rounded end, especially robust threading, stainless steel expansion clamp formed of 3 large pieces, washer with hexagonal nut and head indicating the total length. Installation must be carried out in a properly pre-drilled pilot hole (10 mm hole deeper than the length of the piling with hole diameter = anchor diameter), screwing in the anchor and nut by hand, applying a torque coupling in accordance with the technical drawings of the project. These indications are given in order to perform supply and installation to the best working standards. 	each	... €/each	... €