

GEMINI

High-adhesiveness double-sided nail point sealant tape

Closed cell polyethylene (PE) foam profile with double layer of acrylic glue and separation layer



DOUBLE SECURITY

Double adhesiveness guarantees continuous adhesion between the membrane and batten, avoiding water accumulation in drilled points



HERMETIC

The closed cell polyethylene structure ensures the opening created by the fixing systems is waterproof



CODES AND DIMENSIONS

code	ex code	s [mm]	B [mm]	L [m]	pcs/box
GEMINI80	D62302	3	80	30	10
GEMINI60	D62303	3	60	30	8

TECHNICAL SPECIFICATIONS

property	standard	value
Specific weight	ISO 845	approx. 30 kg/m ³
Tear strength MD/CD	ISO 1926	325 / 220 kPa
Elongation MD/CD	ISO 1926	125 / 115 %
Compression strength	ISO 3386/1	2 kPa at 10 % compression
	ISO 3386/1	3 kPa at 25 % compression
	ISO 3386/1	5 kPa at 50 % compression
Reaction to fire	DIN 4102	class B2
Water absorbancy	ISO 2896	< 2 % vol.
Thermal conductivity	-	0.04 W/mK (a +10 °C)
Temperature resistance	-	-30 / +80 °C
Application temperature	-	+5 / +40 °C
Storage temperature	-	+5 / +25 °C
Solvents	-	NO
VOC emissions	-	< 0.02 % (class A+)

NOTE: Store the product in a dry, covered location