

AOS01 + SIANK 4



ANCHOR POINT FOR STANDING SEAM METAL ROOFS

ROBUST

Fixed on two crimps for improved resistance.

HIGH PERFORMANCE

Up to four workers can be attached.

SAFETY


Installation does not require the sheet metal to be drilled, thanks to the gripper which distributes the load over the double seam, thus ensuring the integrity of the building envelope.



LOAD DIRECTION



TYPES OF APPLICATION



TECHNICAL DATA*

substructure	minimum thickness
 Fe	0,5 mm
 Al	0,7 mm
 Cu	0,5 mm

substructure	minimum thickness
 Zn - Ti	0,7 mm
 stainless steel	0.4 mm

* The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a calculation report with minimum distances according to the relevant standard requirements, the substructure must be checked by a qualified engineer before installation.

SIANK 4 | CODES AND DIMENSIONS

A2
AISI 304

CODE	material	B [mm]	H [mm]	L [mm]	pcs
SIANK4	AISI 304 stainless steel grade 1.4301	430-600	90	400	1
SIANK465	AISI 304 stainless steel grade 1.4301	430-600	113	400	1
AOS01	AISI 304 stainless steel grade 1.4301	60	-	98	1

