

SBN - SBN A2 | AISI304

SELF-DRILLING METAL SCREW

TIP FOR METAL


Special self-perforating tip for iron and steel in thicknesses ranging from 1/32" to 3/16". Ideal for fastening overlapping sections of metal and sheet metal.

FINE THREAD

Fine thread ideal for precise fastening on sheet metal or for metal-to-metal or timber-to-metal couplings.

STAINLESS STEEL

Also available in a bimetal version with head and body in A2 | AISI304 stainless steel and tip in carbon steel. Ideal for outdoor fastening of clips on aluminium supports.



DIAMETER [in]

0.14 **0.14** 0.22 0.32

LENGTH [in]

1 **1** 1 15/16 9 1/2

MATERIAL


Zn
ELECTRO
PLATED

electrogalvanized
carbon steel



A2
AISI 304

A2 | AISI304
austenitic stainless
steel (CRC II)



FIELDS OF USE

Direct fastening, without pre-drill, of metal structural elements to steel substructures (maximum thickness: 3/16").

CODES AND DIMENSIONS

SBN

d ₁ [mm] [in]	CODE	L		b		A	s	pcs
		[mm]	[in]	[mm]	[in]	[in]	[in]	
3,5 0.14 #6 TX 15	SBN3525	25	1	16	5/8	5/8	1/32 - 1/16	500
3,9 0.16 #7 TX 15	SBN3932	35	1 3/8	27	1 1/16	7/8	1/32 - 1/8	200
4,2 0.17 #8 TX 20	SBN4238	38	1 1/2	30	1 3/16	1 1/8	1/16 - 1/8	200
4,8 0.19 #10 TX 25	SBN4845	45	1 3/4	34	1 5/16	1 5/16	1/16 - 3/16	200
5,5 0.22 #12 TX 25	SBN5550	50	1 15/16	38	1 1/2	1 1/2	1/16 - 3/16	200

SBN A2 | AISI304


d ₁ [mm] [in]	CODE	L		b		A	s	pcs
		[mm]	[in]	[mm]	[in]	[in]	[in]	
3,5 0.14 #6 TX 15	SBNA23525	25	1	16	5/8	13/16	1/32 - 1/16	1000
3,9 0.16 #7 TX 15	SBNA23932	32	1 1/4	24	15/16	1	1/32 - 1/8	1000

s thickness that can be drilled, metal plate (steel or aluminium)


GEOMETRY

Nominal diameter	d ₁ [in] ⁽¹⁾	SBN					SBN A2	
		0.14	0.16	0.17	0.19	0.22	0.14	0.16
Outer thread diameter	d ₁ [mm]	3,5	3,9	4,2	4,8	5,5	3,5	3,9
	[in]	0.138	0.154	0.165	0.189	0.217	0.138	0.154
Head diameter	d _K [in]	0.256	0.295	0.311	0.366	0.417	0.287	0.295
Root diameter	t ₁ [in]	0.102	0.150	0.142	0.154	0.161	0.134	0.150
Tip length	L _p [in]	0.197	0.205	0.244	0.260	0.295	0.193	0.205

⁽¹⁾The nominal diameter of the screw is converted into imperial units and rounded up to the nearest decimal point.



INSTALLATION



RECOMMENDATIONS FOR SCREWING:

steel: v_S ≈ 1000 - 1500 rpm
aluminium: v_A ≈ 600-1000 rpm



SBN A2 | AISI304

Ideal for outdoor fastening to standard Rothoblaas aluminium clips.

See CLIP for decks from page 386.