## **MANICA POST**

# ADHESIVE SEALING SLEEVE FOR OUTDOORS

- Aluminium coated for permanent UV stability
- Excellent butyl adhesion
- Resistant to thermal stress





#### ■ CODES AND DIMENSIONS

| CODE     | В    | Н    | Ø     | В    | Н    | Ø       | colour    |   |
|----------|------|------|-------|------|------|---------|-----------|---|
|          | [mm] | [mm] | [mm]  | [in] | [in] | [in]    |           |   |
| MANPOST1 | 300  | 200  | 25/32 | 11.8 | 7.9  | 1.0/1.3 | brown     | 5 |
| MANPOST2 | 300  | 200  | 42/55 | 11.8 | 7.9  | 1.7/2.2 | brown     | 5 |
| MANPOST3 | 230  | 230  | 42/55 | 9.1  | 9.1  | 1.7/2.2 | aluminium | 4 |

Waste classification (2014/955/EU): 17 09 04.

## **MANICA LEAD**

### LEAD PROFILE WITH EPDM SLEEVE

- Excellent for waterproofing lifeline supports such as TOWER
- It can be used on roofs with different slopes
- Perfectly sealed EPDM sleeve



#### **■ CODES AND DIMENSIONS**

| CODE    | s    | В    | L    | Ø    | S     | В    | L    | Ø    | material            |     |
|---------|------|------|------|------|-------|------|------|------|---------------------|-----|
|         | [mm] | [mm] | [mm] | [mm] | [mil] | [in] | [in] | [in] |                     |     |
| MANEPDM | -    | -    | -    | 48   | -     | -    | -    | 1.9  | EPDM                | 150 |
| MANLEAD | 1    | 310  | 405  | -    | 39    | 12.2 | 15.9 | -    | lead <sup>(1)</sup> | 5   |

 $^{\hbox{(1)}}$  Avoid contact with skin, eyes and food. Do not produce and breathe dust. Waste classification (2014/955/EU): 17 04 03.