

RIDGE

NET ROLL

FLEXIBLE VENTILATED UNDER-RIDGE

FLEXIBLE

The polypropylene ventilation fabric ensures excellent adaptability during installation.

DOUBLE SECURITY

The ventilation strip, which is sewn and glued to the pleated wings, guarantees that the solution remains intact during installation and continues to be effective over time.



TECHNICAL DATA

Properties	value	USC units
Air passage	approx. 150 cm ² /m	7.09 in ² /ft
Elongation capacity (pleated aluminium strips)	approx. 45 %	-
Butyl tape width	15 mm	0.6 in
Butyl tape thermal resistance	-40 / +90 °C	-40 / +194 °F
Application temperature	+5 / +40 °C	+41 / +104 °F
UV resistance (aluminium straps)	permanent	-
Storage temperature ⁽¹⁾	+5 / +30 °C	+41 / +86 °F

⁽¹⁾ Keep the product in a dry, covered location.

 Waste classification (2014/955/EU): 17 09 04.

CODES AND DIMENSIONS

CODE	B [mm]	L [m]	B [in]	L [ft]	colour	RAL	
NETRED310	310	5	12.2	16	brick red	8004	4
NETBRO310	310	5	12.2	16	brown	8019	4
NETBLA310	310	5	12.2	16	black	9005	4
NETRED390	390	5	15.4	16	brick red	8004	4
NETBRO390	390	5	15.4	16	brown	8019	4
NETBLA390	390	5	15.4	16	black	9005	4
NETRED39020	390	20	15.4	66	brick red	8004	1
NETBRO39020	390	20	15.4	66	brown	8019	1
NETBLA39020	390	20	15.4	66	black	9005	1



EASY TO SHAPE

Aluminium straps and butyl tape ensure adaptability to the profile of the roof elements.

MATERIALS

Aluminium, PP non-woven fabric, butyl tape.