


TILE STOP L

L PRE-SHAPED HOOKS FOR PLAIN TILES

- Dry installation
- Tough and secure hold for the first row of tiles on the pitch
- They can be used as mullion hooks on which the weight of the upper rows of tiles can be unloaded
- Installation with foam or mortar is avoided in compliance with standard UNI 9460
- Wide range of materials and sizes available



CODES AND DIMENSIONS

CODE	L [mm]	H [mm]	L [in]	H [in]	material	colour	RAL	
TSLI28016 ⁽¹⁾	280	16	11.0	0.6	steel AISI 204	steel	-	200
TSLI28020 ⁽¹⁾	280	20	11.0	0.8	steel AISI 204	steel	-	200
TSLRED28016 ⁽¹⁾	280	16	11.0	0.6	pre-painted metal sheet	Siena red	3009	200
TSLRED28020 ⁽¹⁾	280	20	11.0	0.8	pre-painted metal sheet	Siena red	3009	200
TSLBRO28016 ⁽¹⁾	280	16	11.0	0.6	pre-painted metal sheet	brown	8019	200
TSLBRO28020 ⁽¹⁾	280	20	11.0	0.8	pre-painted metal sheet	brown	8019	200
TSLCOP28016 ⁽¹⁾	280	16	11.0	0.6	stainless steel tape	copper	-	200
TSLCOP28020 ⁽¹⁾	280	20	11.0	0.8	stainless steel tape	copper	-	200

⁽¹⁾Products available only upon order.

 Waste classification (2014/955/EU): 17 04 05.

RECOMMENDATIONS FOR INSTALLATION

