

BRUSH VENT

ČVRSTO PODSLJEME S BOČNIM ČETKAMA

BRZO POSTAVLJANJE

Zahvaljujući mekanim čekinjama, jednostavno se prilagođava pokrovnom profilu a da nije potrebno modeliranje.

ZAŠTITA

Čekinjama se omogućuje učinkovita zaštita od prodiranja vode i stranih elemenata.



TEHNIČKI PODATCI

Svojstvo	vrijednost	USC units
Materijali	PVC	–
Dužina češljeva	60 mm	2.36 in
Prolazak zraka	$\geq 200 \text{ cm}^2/\text{m}$	$\geq 9.45 \text{ in}^2/\text{ft}$
Otpornost na ultraljubičaste (UV) zrake	trajno	–
Toplinska otpornost	-20 / +80 °C	-4 / +176 °F

 Razvrstavanje otpada (2014/955/EU): 17 02 03.

KODOVI I DIMENZIJE

KOD	B [mm]	H [mm]	L [m]	B [in]	H [in]	L [ft]	boja	RAL	
BRUVENRED175	175	75	1	6.9	3.0	3	crvena boja opeke	8004	20
BRUVENBRO175 ⁽¹⁾	175	75	1	6.9	3.0	3	smeđa	8019	20
BRUVENBLA175	175	75	1	6.9	3.0	3	crna	9005	20

⁽¹⁾Proizvod je dostupan samo na narudžbu.

SAVJETI ZA POLAGANJE

