


TILE STOP L

PRETHODNO OBLIKOVANE KUKE U OBLIKU SLOVA L ZA GLATKE CRJEPOVE

- Polazu se na suho
- Čvrsto i sigurno zahvaćanje za prvi red crjepova nagiba
- Mogu se upotrebljavati kao poprečne kuke na koje se prebacuje težina gornjih redova crjepova
- Izbjegava se polaganje s pjenom ili mortom prema normi UNI 9460
- Dostupan je širok asortiman materijalâ i dimenzija



KODOVI I DIMENZIJE

KOD	L [mm]	H [mm]	L [in]	H [in]	materijal	boja	RAL	
TSLI28016 ⁽¹⁾	280	16	11.0	0.6	čelik AISI 204	čelik	–	200
TSLI28020 ⁽¹⁾	280	20	11.0	0.8	čelik AISI 204	čelik	–	200
TSLRED28016 ⁽¹⁾	280	16	11.0	0.6	prethodno lakirani lim	crvena boja pigmenta sijena	3009	200
TSLRED28020 ⁽¹⁾	280	20	11.0	0.8	prethodno lakirani lim	crvena boja pigmenta sijena	3009	200
TSLBRO28016 ⁽¹⁾	280	16	11.0	0.6	prethodno lakirani lim	smeđa	8019	200
TSLBRO28020 ⁽¹⁾	280	20	11.0	0.8	prethodno lakirani lim	smeđa	8019	200
TSLCOP28016 ⁽¹⁾	280	16	11.0	0.6	traka od nehrđajućeg čelika	bakar	–	200
TSLCOP28020 ⁽¹⁾	280	20	11.0	0.8	traka od nehrđajućeg čelika	bakar	–	200

⁽¹⁾Proizvod je dostupan samo na narudžbu.

 Razvrstavanje otpada (2014/955/EU): 17 04 05.

SAVJETI ZA POLAGANJE

