

# D 38 RLE

## 4-SPEED DRILL DRIVER

### HIGH PERFORMANCE

Powerful and resistant 2000 W motor, able to reach a tightening torque of > 250 Nm at 1st speed.

Continuously variable speed adjustment in every gear.

### MAINTENANCE-FREE

4-Speed transmission with continuous lubrication.

Convenient positioning of right/left rotation switching and speed regulator.



### CODES AND DIMENSIONS

| CODE       | description                                              | pcs |
|------------|----------------------------------------------------------|-----|
| DUD38RLE   | 4-Speed drill driver                                     | 1   |
| RENTD38SET | rental machine for USA<br>(includes DUD38RLE and DUVSKU) | 1   |

Scope of supply: 4-speed machine D 38 RLE, removal wedge in cardboard box. Use of the machine only with the safety clutch (DUVSKU) and the second grip (DUD38SH) is strongly recommended.

### COMPLEMENTARY PRODUCTS

| CODE     | description                                            | pcs |
|----------|--------------------------------------------------------|-----|
| DUVSKU   | VSKU clutch                                            | 1   |
| DUD38SH  | screw handle D38SH                                     | 1   |
| DUD322   | adapter 1 for MK3                                      | 1   |
| ATCS2010 | adapter 2 for sleeve                                   | 1   |
| DUF13    | tightening range of chuck mandrel 5-20 mm              | 1   |
| ATCS007  | sleeves for RTR structural reinforcement system Ø16 mm | 1   |
| ATCS008  | sleeves for RTR structural reinforcement system Ø20 mm | 1   |

### TECHNICAL DATA

| Properties                                    | values                        |
|-----------------------------------------------|-------------------------------|
| Rated power consumption                       | 2000 W                        |
| Drilling Ø on:                                |                               |
| - solid drill bit for steel                   | up to 32 mm   up to 1.26 in   |
| - solid drill bit for wood                    | up to 130 mm   up to 5.12 in  |
| - polypropylene with LS hole cutter           | up to 600 mm   up to 23.62 in |
| Rpm under load in 1st, 2nd, 3rd and 4th speed | 120/210/380/650 U/min         |
| Machine weight                                | 8.6 kg   18.96 lbs            |
| Collar diameter Ø                             | 70 mm   2 3/4"                |
| Drill chuck connection                        | conical MK 3                  |



## COMPLEMENTARY PRODUCTS - ACCESSORIES

### FRICTION

- Tightening torque 200 Nm | 147.5 ft-lbs
- Square connection 1/2"

| CODE   | pcs |
|--------|-----|
| DUVSKU | 1   |



### SCREW HANDLE

- High security

| CODE    | pcs |
|---------|-----|
| DUD38SH | 1   |



### ADAPTER 1

- For MK3

| CODE   | pcs |
|--------|-----|
| DUD322 | 1   |



### ADAPTER 2

- For sleeve

| CODE     | pcs |
|----------|-----|
| ATCS2010 | 1   |



### SLEEVES

- For WB structural reinforcement system

| CODE    | Ø [mm] | Ø [in] | pcs |
|---------|--------|--------|-----|
| ATCS007 | 16     | 0.63   | 1   |
| ATCS008 | 20     | 0.79   | 1   |



### MANDREL

- Adapter 1 (DUD322) is required for connection to the D 38 RLE drill

| CODE  | pcs |
|-------|-----|
| DUF13 | 1   |



## RTR

### STRUCTURAL REINFORCEMENT SYSTEM

| CODE      | d <sub>1</sub><br>[mm] | L<br>[mm] | d <sub>hole</sub><br>[mm] | d <sub>1</sub><br>[in] | L<br>[in] | d <sub>hole</sub><br>[in] | pcs |
|-----------|------------------------|-----------|---------------------------|------------------------|-----------|---------------------------|-----|
| RTR162200 | 16                     | 2200      | 13                        | 0.63                   | 86.6      | 0.52                      | 10  |
| RTR202200 | 20                     | 2200      | 16                        | 0.79                   | 86.6      | 0.63                      | 5   |



For more information, see the "TIMBER SCREWS AND DECK FASTENING" catalogue, available in the "Catalogues" section of the website [www.rothoblaas.com](http://www.rothoblaas.com).