

Specifications:

Spec. n.	Description	Unit of measurement	Price per unit	Total price
1	SMOOTH PINS STA - S235JR: Supply and installation, as provided for in the technical drawings of the project, of smooth pins, with diameter $\varnothing = \dots$ mm and length $L = \dots$ mm, STA-SMOOTH PIN DIN 1052 produced and marketed by Rotho Blaas srl (www.rothoblaas.com), having the following characteristics: - class S235JR steel with $f_{u,k} \geq 360$ N/mm² - hot-dip galvanising for immersion for continuous immersion with minimum thickness 50 μm - countersunk end - CE marking for construction products in accordance with Directive 89/106/EEC, in accordance with EN 14592:2008 The pins must also be calibrated and straightened. Installation is carried out by means of manual hammering in a properly pre-drilled pilot hole (with hole diameter = pin diameter). These indications are given in order to perform supply and installation to the best working standards. 	each	... €/each	... €

Spec. n.	Description	Unit of measurement	Price per unit	Total price
1	SMOOTH PINS STA - S355JR: Supply and installation, as provided for in the technical drawings of the project, of smooth pins, with diameter $\varnothing = \dots$ mm and length $L = \dots$ mm, STA-SMOOTH PIN DIN 1052 produced and marketed by Rotho Blaas srl (www.rothoblaas.com), having the following characteristics: - class S355JR steel with $f_{u,k} \geq 470$ N/mm² - hot-dip galvanising for immersion for continuous immersion with minimum thickness 50 μm - countersunk end - CE marking for construction products in accordance with Directive 89/106/EEC, in accordance with EN 14592:2008 The pins must also be calibrated and straightened. Installation is carried out by means of manual hammering in a properly pre-drilled pilot hole (with hole diameter = pin diameter). These indications are given in order to perform supply and installation to the best working standards. 	each	... €/each	... €