

DRAGON

LIFTING STRAP WITH TILTING SYSTEM

- Reusable lifting system ideal for Timber Frame elements
- Certified for lifting and reusable according to EN 1492-1 with a safety factor of 7:1
- Hole required in the element: 45 mm



CODES AND DIMENSIONS

CODE	size		WLL						pcs
									
	[mm]	[in]	[kg]	[lbs]	[kg]	[lbs]	[kg]	[lbs]	
DRAGON	35 x 500	1 3/8 x 19 3/4	850	1875	595	1310	425	935	1



OCTOPUS

LIFTING EYEBOLT AND PERCUSSION NUT

- Eyebolts can be used again
- Limited wear



LIFTING EYEBOLTS

CODE	thread	rope diameter		L		capacity		colour mark	pcs
		[mm]	[in]	[mm]	[in]	[kg]	[lbs]		
OCT45512	M12	6,0	0.236	455	17 15/16	500	1100	orange	1
OCT45516	M16	8,0	0.315	455	17 15/16	1200	2645	red	1
OCT45520	M20	10,0	0.394	455	17 15/16	2000	4410	green	1

PERCUSSION NUT

CODE	thread	Ø hole		H		Ø flange		colour mark	pcs
		[mm]	[in]	[mm]	[in]	[mm]	[in]		
OCTM12	M12	18	3/4	14	9/16	60	2 3/8	orange	50
OCTM16	M16	22	7/8	16	5/8	60	2 3/8	red	50
OCTM20	M20	24	15/16	16	5/8	60	2 3/8	green	50

Percussion nut that can be used once in a single lifting cycle.

