

I PATROL ON WALL

WALL-MOUNTED LIFELINE ON STEEL AND CONCRETE

MINIMALIST DESIGN

The size of the components minimises the aesthetic impact of the safety device on the wall.

FUNCTIONAL

Thanks to the different components availability, it is possible to create customised lifelines according to site requirements.

PRACTICAL

It can be used components that allow the operator to overcome intermediate points and curves by means of a sliding device.

EN 795:2012 C	CEN/TS 18415:2013	UNI 11578:2015 C	AS/NZS 1891.4:2009	AS/NZS 1891.2:2001	CSA Z259.16
---------------------	----------------------	------------------------	-----------------------	-----------------------	----------------

CSA Z259.16 READY
Validated through testing





MAXIMUM NUMBER
OF USERS




LOAD DIRECTION



TYPES OF
APPLICATION



PATROL LIFELINE COMPONENTS



A4
AISI 316

NOTE:

For versions in A4, see the page on components (see page 56).

TECHNICAL DATA*


PATROLEND | PATROLEND A4





substructure	minimum thickness	fasteners
C20/25	116 mm	INA 5.8 M16 VIN-FIX
	170 mm	SKR Ø16
	170 mm	AB1 M16
S235JR	5 mm	DIN 933 M16 DIN 125-1A M16 MUT AI 985 M16

PAREND | PAREND A4

substructure	minimum thickness	fasteners
C20/25	98 mm	INA 5.8 M12 VIN-FIX
	130 mm	SKR Ø12
	140 mm	AB1 M12
S235JR	5 mm	DIN 933 M12 DIN 125-1A M12 MUT AI 985 M12

* The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a correct calculation report with minimum distances according to the standard requirements, the substructure must be checked by a qualified engineer before installation.



		SPEAR					SPEAREVO				
		EN 795:2012 C	CEN/TS 16415:2013	UNI 11578:2015 C	AS/NZS 1891.2:2001	AS/NZS 1891.4:2009	EN 795:2012 C	CEN/TS 16415:2013	UNI 11578:2015 C	AS/NZS 1891.2:2001	AS/NZS 1891.4:2009
users	no.			 (SPAN)					 (SPAN)		
minimum span	x_{min} [m]	2		2			2		2		
maximum span	x_{max} [m]	7,5		7,5			15		15		
maximum deflection	y_{max} [m]	1,40		1,40			3,40		3,40		

END ELEMENTS | CODES AND DIMENSIONS

CODE	description	material		B [mm] [in]	H [mm] [in]	L [mm] [in]	s [mm] [in]	pcs	
PATROLEND	end element	AISI 304 stainless steel grade 1.4301	A2 AISI 304	40 1 9/16	61 2 3/8	66 2 5/8	6 0.24	1	
PATROLEND A4	A4 end element	AISI 316 stainless steel grade 1.4401	A4 AISI 316	40 1 9/16	61 2 3/8	66 2 5/8	6 0.24	1	
PAREND	end element	AISI 304 stainless steel grade 1.4301	A2 AISI 304	300 11 3/4	150 6	300 11 3/4	-	1	
PAREND A4	A4 end element	AISI 316 stainless steel grade 1.4401	A4 AISI 316	300 11 3/4	150 6	300 11 3/4	-	1	