

NDS

PREDĹŽENÁ HMOŽDINKA SO SKRUTKOU

- Plastová kotva pre aplikáciu do poloplnného a dierovaného muriva
- Fixovanie priechodné
- Kompletná so zápusťou skrutky zo zinkovanej ocele
- Anti-rotáčne krídla



KÓDY A ROZMERY

KÓD	d ₀ [mm]	L _t [mm]	d _v x L _v [mm]	t _{fix} [mm]	h _{1,min} [mm]	bit	ks
NDS10100	10	100	7 x 105	25	85	TX 40	25
NDS10120		120	7 x 125	45	85	TX 40	25
NDS10140		140	7 x 145	65	85	TX 40	25
NDS10160		160	7 x 165	85	85	TX 40	25
NDS10200		200	7 x 205	125	85	TX 40	25

NDB

PREDĹŽENÁ HMOŽDINKA S PRÍRAZOM A KLINCovou SKRUTKOU


- Plastová hmoždinka so zapusteným golierom
- Fixovanie priechodné
- Kompletná kľincová skrutka so zapustenou hlavou zinkovaná oceľ



KÓDY A ROZMERY

KÓD	d ₀ [mm]	L _t [mm]	d _v x L _v [mm]	t _{fix} [mm]	h _{1,min} [mm]	h _{ef} [mm]	d _k [mm]	bit	ks
NDB640	6	40	3,8 x 45	10	30	27	10,0	PZ 2	200
NDB655		55	3,8 x 60	25	30	27	10,0	PZ 2	100
NDB667		67	3,8 x 72	37	30	27	10,0	PZ 2	100
NDB860	8	60	4,8 x 65	25	40	35	12,2	PZ 3	100
NDB875		75	4,8 x 80	40	40	35	12,2	PZ 3	100
NDB8100		100	4,8 x 105	65	40	35	12,2	PZ 3	50
NDB8120		120	4,8 x 125	85	40	35	12,2	PZ 3	50
NDB8135		135	4,8 x 140	100	40	35	12,2	PZ 3	50

GEOMETRIA



- d₀ priemer kotevného prvku = priemer otvoru v betónovom podklade
- L_t dĺžka kotvy
- d_v x L_v priemer skrutky x dĺžka skrutky
- t_{fix} maximálna hrúbka fixovania
- h₁ minimálna hĺbka otvoru
- h_{ef} efektívna hĺbka kotvy
- d_k priemer hlavy