

TEMPORARY ANCHOR SYSTEMS

BAND23

RING WEBBING LOAD 23 kN

EAC CE

CODES AND DIMENSIONS

CODE	standard	L		weight	Q _r	colour	pcs
		[m]	[ft]	[g]	[kN]		
BAND2340	CE - EN 795/B EN 354 - EN 566	0,4	1' 3 3/4"	28	23	●	1
BAND2360	CE - EN 795/B EN 354 - EN 566	0,6	1' 11 5/8"	45	23	●	1
BAND2380	CE - EN 795/B EN 354 - EN 566	0,8	2' 7 1/2"	60	23	● ●	1
BAND23120	CE - EN 795/B EN 354 - EN 566	1,2	3' 11 1/4"	90	23	● ●	1
BAND23180	CE - EN 795/B EN 354 - EN 566	1,8	5' 10 7/8"	135	23	●	1



BAND35

RING WEBBING LOAD 35 kN

EAC CE

CODES AND DIMENSIONS

CODE	standard	L		weight	Q _r	colour	pcs
		[m]	[ft]	[g]	[kN]		
BAND3530	CE - EN 795/B - EN 354 ANSI/ASSE Z359.18	0,3	1'	52	35	●	1
BAND3560		0,6	1' 11 5/8"	95	35	●	1
BAND3580		0,8	2' 7 1/2"	130	35	●	1
BAND35120		1,2	3' 11 1/4"	185	35	●	1
BAND35150		1,5	4' 11"	230	35	●	1
BAND35180		1,8	5' 10 7/8"	270	35	●	1



RIG

ANCHOR MULTIPLIER

EAC CE

- Anchor multiplier designed to organise a work space and create an easy-to-use system of multiple anchors
- Made of light aluminium alloy

CODES AND DIMENSIONS

CODE	standard	material	n° anchor system	∧ [kN]	pcs
RIG3	CE UIAA 130 V1	aluminium alloy	3	36	1
RIG4	CE UIAA 130 V1	aluminium alloy	4	36	1

Also available in the EAC version



RIG3



RIG4