


CONNECTORS

RISE AUTOMATIC LOCKING GATE




two-step opening

RISE LOCK



significantly reduces the risk of accidental opening

TWIST LOCK



CLASSIC



OVAL CONNECTOR

- Oval connector available in aluminium and carbon steel, with a circular body that makes it ideal for use with mobile devices (pulleys, clamps, fall protection, etc.)
- Equipped with screw ring nut

CODES AND DIMENSIONS

CODE	standard	weight [g]	<> [kN]	∧ [kN]	⌋ [kN]	pcs
CLASTE	CE - EN 362/B	176	24	7	6	1
CLAALU	CE - EN 362/B - EN 12275/B - EAC	65	22	7	7	1



CLASTE



CLAALU

OVAL



CONNECTOR FOR CONNECTION TO FIXED POINTS

- Oval-shaped wide-opening connector, ideal for severe conditions and for connection to structural anchor points, lifelines, etc.
- ANSI certified high load connector
- Includes autoblock system

CODES AND DIMENSIONS

CODE	standard	weight [g]	<> [kN]	∧ [kN]	pcs
OVALSTE	CE - EN 362/M	215	40	15	1
OVALALU	CE - EN 362/B - EN 12275/B - EAC	76	26	9	1
OVALANS	CE - EN 362/M - ANSI Z359.12	220	40	20	1
OVALA4	CE - EN 362/B	230	27	7	1
OVALRISE	CE - EN 362/M	220	40	15	1



OVALSTE



OVALALU



OVALANS



OVALA4



OVALRISE