

# DESCENDERS AND CLAMPS

## ROPE BRAKE



### DESCENDER

- Simple easy to manoeuvre activation catch that guarantees more fluid and precise operation
- Allows two people to be lowered simultaneously for rescue operations
- Allows the cord to be recovered for ascent
- Use with Ø10-12 mm rope max. load 100 kg
- Use with Ø11-12 mm rope max. load 200 kg



### CODES AND DIMENSIONS

| CODE   | standard                 | weight | rope diameter |             | pcs |
|--------|--------------------------|--------|---------------|-------------|-----|
|        |                          | [g]    | [mm]          | [in]        |     |
| ROPBRA | CE - EN 341 - EN 12841/C | 480    | Ø10/Ø12       | Ø0.39-Ø0.47 | 1   |

Also available in the EAC version.

## ROPE BRAKE 2



### DESCENDERS FOR RESCUE WITH CONNECTORS

- Maximum capacity: 200 kg
- Steel carabiners with screw ring nut included
- Practical bag for transport included
- Evacuation and rescue device that is used together with individual fall protection equipment
- Appropriate for rescue operations in the case of injured or unconscious workers



### CODES AND DIMENSIONS

| CODE    | standard      | L   |            | rope diameter |       | pcs |
|---------|---------------|-----|------------|---------------|-------|-----|
|         |               | [m] | [ft]       | [mm]          | [in]  |     |
| ROPBRA2 | CE - EN 341/D | 20  | 65' 7 3/8" | Ø11           | Ø0.43 | 1   |