

CAP PLUS

TARPAULIN FOR ROOFS

- Good mechanical characteristics resistant to both tension and tearing
- Thanks to the metal fastening eyelets positioned every metre, it is possible to fix the tarpaulin firmly to the roof

CODES AND DIMENSIONS

CODE	sizes		weight		pcs
	[m]	[ft]	[kg]	[lbs]	
CAPPLUS0810	8 x 10	26 x 33	24,0	52.9	1
CAPPLUS1012	10 x 12	33 x 39	36,0	79.4	1
CAPPLUS1214	12 x 14	39 x 46	50,4	111.1	1
CAPPLUS1416	14 x 16	46 x 52.5	67,2	148.2	1
CAPPLUS1618	16 x 18	52.5 x 59	86,4	190.5	1

TECHNICAL DATA

Properties	standard	values
Mass per unit area	ISO 2286-2	300 g/m ²
Thickness	ISO 2286-3	0.4 mm
Tensile strength (transverse and longitudinal)	ISO 1421-1	1200/1000 N/50 mm
Tear strength (transverse and longitudinal)	ISO 1421-1	130/80 N/50 mm



CAP ECO

TARPAULIN FOR ROOFS

- The black inner fabric gives better resistance to UV rays
- Thanks to the metal fastening eyelets positioned every metre, it is possible to fix the tarpaulin firmly to the roof

CODES AND DIMENSIONS

CODE	sizes		weight		pcs
	[m]	[ft]	[kg]	[lbs]	
CAPECO0410	4 x 10	13 x 32	8,4	18.5	1
CAPECO0810	8 x 10	26 x 33	16,8	37.0	1

TECHNICAL DATA

Properties	standard	values
Mass per unit area	ISO 2286-2	210 g/m ²
Thickness	ISO 2286-3	0,27 mm
Tensile strength (transverse and longitudinal)	ISO 1421-1	980/920 N/50 mm
Tear strength (transverse and longitudinal)	ISO 1421-1	120/75 N/50 mm

