

WEB BUILD

POLYURETHANE CONSTRUCTION ADHESIVE

- Universal: suitable for windows, doors, stairs and industrial applications; solvent-free
- Hardens into sandable and paintable joints
- Expands during curing

CODES AND DIMENSIONS

CODE	content		colour	pcs
	[ml]	[US fl oz]		
WEBBUILD	310	10.48	beige	1

Compatible cartridge gun: FLY, FLY POWER, FLY SOFT POWER.

TECHNICAL DATA

Properties	values
Minimum application temperature	+7°C
Quantity to be applied (depending on the support)	approx. 100 - 200 ml/m ²
Heat bonding strength according to EN 14257 (WATT 91)	approx. 7,1 N/mm ²
Setting time: filling bonding at +20°C (at 60 °C)	22 min (7 min)
Skin formation	approx. 2 - 5 min
Setting time: filling bonding at +20°C (at 60 °C)	22 min (7 min)
Setting time: surfaces bonding at +20°C (at 60 °C)	15 min (10 min)
Pressure	approx. 1,0 N/mm ²
Storage: if closed, max. 12 months at temperatures from	+15°C at +25°C



WEB PU

POLYURETHANE ADHESIVE

- Universal polyurethane glue for construction and industrial use
- Suitable for rigid PVC, sanded GRP, aluminium, PUR foams and pre-treated mineral wool
- Solvent-free and expands during curing
- Hardens into sandable and paintable joints

CODES AND DIMENSIONS

CODE	content		colour	pcs
	[g]	[lbs]		
WEBPU	500	1.10	brown	1

TECHNICAL DATA

Properties	values
Minimum application temperature	+7°C
Quantity to be applied (depending on the support)	approx. 100 - 350 g/m ²
Heat bonding strength according to EN 14257 (WATT 91)	approx. 8,5 N/mm ²
Film formation after	approx. 25 - 35 min
Setting time: timber-to-timber bonding at +20 °C	90 min
Storage: if closed, max. 12 months at temperatures from	+15°C at +25°C

