

# BST

## DRILLING STATION

- Collar diameter **Ø43 mm | 1 11/16"**
- Bit guide fastening: **8 - 30 mm | 5/16" - 1 3/16"**
- Tiltable version, adjustable up to 45° on both sides



MA961210/MA961211



MA961215/MA961216

### CODES AND DIMENSIONS

| CODE     | description                         | pcs |
|----------|-------------------------------------|-----|
| MA961210 | fixed BST 320 drilling station      | 1   |
| MA961211 | fixed BST 460 drilling station      | 1   |
| MA961215 | tiltable BST 460 S drilling station | 1   |
| MA961216 | tiltable BST 650 S drilling station | 1   |

### TECHNICAL DATA

| properties                |               | BST 320       | BST 460       | BST 460 S      | BST 650 S       |
|---------------------------|---------------|---------------|---------------|----------------|-----------------|
| Max. tool diameter at 0°  | [mm]<br>[in]  | 130<br>5 1/8  | 130<br>5 1/8  | 130<br>5 1/8   | 130<br>5 1/8    |
| Max. tool diameter at 45° | [mm]<br>[in]  | -             | -             | 100<br>4       | 100<br>4        |
| Max. tip length           | [mm]<br>[in]  | 320<br>12 5/8 | 460<br>18 1/8 | 460<br>18 1/8  | 650<br>25 9/16  |
| Max. hole depth           | [mm]<br>[in]  | 160<br>6 1/4  | 300<br>11 3/4 | 265<br>10 7/16 | 455<br>17 15/16 |
| Weight                    | [kg]<br>[lbs] | 4,5<br>9.9    | 4,8<br>10.6   | 5<br>11.0      | 5,4<br>11.9     |



### LEWIS

TWIST DRILL BITS FOR DEEP DRILLING IN SOFT  
 AND EUROPEAN HARDWOODS

See the product on page 236

