

# COMPRESSOR 50

CE  
DM 2006/42/CE

## LARGE OIL-FREE COMPRESSOR WITH 50 L RUSTPROOF TANK

### LONG SERVICE LIFE GUARANTEED

The special internal coating of the tank protects against corrosion caused by condensation, ensuring strength and durability even under intensive use.

### GREATER STABILITY ON UNEVEN GROUND

Thanks to the lower centre of gravity, the horizontal compressor is more stable and less prone to tipping, making it particularly suitable for construction sites with uneven terrain.

### LARGE CAPACITY

Ideal for large compressed-air devices with high air consumption or for simultaneous operation of two medium-sized tools thanks to the dual connections.



### CODES AND DIMENSIONS

| CODE     | description                         | pcs |
|----------|-------------------------------------|-----|
| 1 COMP50 | compressor with 50 L rustproof tank | 1   |

### TECHNICAL DATA

| Properties                 | values                                            |
|----------------------------|---------------------------------------------------|
| Supply voltage             | 230 V                                             |
| Rated power                | 1,1 kW                                            |
| Frequency                  | 50 Hz                                             |
| Maximum operating pressure | 8 bar   115 psi                                   |
| Safety valve               | 10 bar   145 psi                                  |
| Noise level                | 69 dB                                             |
| Rotation speed             | 1400 rpm                                          |
| Tank volume                | 50 l                                              |
| Inlet air flow rate        | 300 l/min                                         |
| Outlet air flow rate       | 170 l/min                                         |
| Total weight               | 48 kg   105 lbs                                   |
| Dimensions (L x P x H)     | 800 x 350 x 650 mm   31 1/2" x 13 3/4" x 25 9/16" |