

BORMAX GUIDE

PRECISION CUTTER FOR TIMBER

CODES AND DIMENSIONS

CODE	Ø cutter [mm] [in]	Ø inside hole for centring [mm] [in]	Ø shank [mm] [in]	TL [mm] [in]	EL [mm] [in]	pcs
F1614020	20 0.79	8 5/16	13 1/2	140 5 1/2	90 3 1/2	1
F1614025	25 0.98	8 5/16	13 1/2	140 5 1/2	90 3 1/2	1
F1614030	30 1.18	8 5/16	13 1/2	140 5 1/2	90 3 1/2	1
F1614035	35 1.38	8 5/16	13 1/2	145 5 11/16	95 3 3/4	1
F1614040	40 1.58	10 3/8	13 1/2	145 5 11/16	95 3 3/4	1
F1614045	45 1.77	10 3/8	13 1/2	150 6	100 4	1
F1614050	50 1.97	10 3/8	13 1/2	150 6	100 4	1
F1614055	55 2.17	10 3/8	13 1/2	150 6	100 4	1
F1614060	60 2.36	10 3/8	13 1/2	150 6	100 4	1
F1614065	65 2.56	10 3/8	13 1/2	155 6 1/8	105 4 1/8	1
F1614070	70 2.76	10 3/8	13 1/2	155 6 1/8	105 4 1/8	1
F1614075	75 2.95	10 3/8	13 1/2	155 6 1/8	105 4 1/8	1
F1614080	80 3.15	10 3/8	13 1/2	155 6 1/8	105 4 1/8	1
F1614100	100 3.94	10 3/8	16 5/8	160 6 1/4	110 4 3/8	1
F1614110	110 4.33	10 3/8	16 5/8	160 6 1/4	110 4 3/8	1
F1614120	120 4.72	10 3/8	16 5/8	160 6 1/4	110 4 3/8	1

Including a centering drill bit and a hexagonal wrench.



TL total length

EL effective length



DRILL BIT FOR PRE-DRILLING

CODE	Ø shank [mm] [in]	for cutters with Ø [mm] [in]	TL [mm] [in]	EL [mm] [in]	pcs
F1614208	8 5/16	20 - 35 0.79 - 1.38	75 3	50 2	1
F1614210	10 3/8	40 - 120 1.58 - 4.72	75 3	50 2	1



CENTERING DRILL BIT

CODE	Ø [mm] [in]	Ø shank [mm] [in]	for cutters with Ø [mm] [in]	pcs
F1619208	3,15 0.12	8 5/16	20 - 35 0.79 - 1.38	1
F1619210	4,0 0.16	10 3/8	40 - 120 1.58 - 4.72	1



GUIDING PIN

CODE	Ø [mm] [in]	Ø shank [mm] [in]	for cutters with Ø [mm] [in]	TL [mm] [in]	EL [mm] [in]	pcs
F1619008	8 0.32	8 5/16	20 - 35 0.79 - 1.38	75 3	50 2	1
F1619110	10 0.39		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619112	12 0.47		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619114	14 0.55		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619116	16 0.63		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619118	18 0.71		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619120	20 0.79		20 - 35 0.79 - 1.38	75 3	50 2	1
F1619012	12 0.47	10 3/8	40 - 120 1.58 - 4.72	75 3	50 2	1
F1619014	14 0.55		40 - 120 1.58 - 4.72	75 3	50 2	1
F1619016	16 0.63		40 - 120 1.58 - 4.72	75 3	50 2	1
F1619018	18 0.71		40 - 120 1.58 - 4.72	75 3	50 2	1
F1619020	20 0.79		40 - 120 1.58 - 4.72	75 3	50 2	1



DEPTH STOP

CODE	for cutters with Ø [mm] [in]	Ø internal [mm] [in]	pcs
F1619100	40 - 90 0.79 - 3.54	95 3 3/4	1

