

TAP1

ABDECKZAPFEN QUERHOLZ FICHTE

ART.-NR.	Ø [mm]	H [mm]	Stk.
TAP11010	10	10	2000
TAP11210	12	10	1000
TAP11510	15	10	1000
TAP11610	16	10	1000
TAP12010	20	10	560
TAP12510	25	10	345
TAP13010	30	10	260
TAP13510	35	10	180
TAP14010	40	10	140
TAP14510	45	10	105
TAP15010	50	10	75
TAP12010L	20	10	6500
TAP12510L	25	10	4000
TAP13010L	30	10	3000
TAP13510L	35	10	2100
TAP14010L	40	10	1600
TAP15515 ⁽¹⁾	55	15	40
TAP6515 ⁽²⁾	65	15	40

⁽¹⁾ Zum Schließen der Ausfräsung Ø55 mm von WASP.

⁽²⁾ Zum Schließen der Ausfräsung Ø65 mm von WASPL.



TAP2

ABDECKZAPFEN QUERHOLZ LÄRCH

ART.-NR.	Ø [mm]	H [mm]	Stk.
TAP21010	10	10	1890
TAP21510	15	10	745
TAP22010	20	10	405
TAP22510	25	10	275
TAP23010	30	10	180
TAP23510	35	10	140
TAP24010	40	10	100
TAP24510	45	10	88
TAP25010	50	10	73



TAP3

ABDECKZAPFEN NATURAST FICHTE

ART.-NR.	Ø [mm]	H [mm]	Stk.
TAP3109	10	9	250
TAP3159	15	9	250
TAP3209	20	9	250
TAP3259	25	9	250
TAP3309	30	9	250
TAP3359	35	9	250
TAP3409	40	9	100
TAP3509	50	9	100



TAP4

ZAPFEN AUS FICHTENHOLZ, QUERHOLZ,
FÜR FEUERWIDERSTAND R-30 GEMÄSS EN 1995-1-2^[*]

ART.-NR.	Ø [mm]	H [mm]	Stk.
TAP41220	12	20	100
TAP41620	16	20	100
TAP42020	20	20	100
TAP42520	25	20	100
TAP43020	30	20	100
TAP44020	40	20	100
TAP45020	50	20	50
TAP46020	60	20	40
TAP47020	70	20	25
TAP48020	80	20	25
TAP49020	90	20	15
TAP410020	100	20	10
TAP41240	12	40	450
TAP41640	16	40	250
TAP42040	20	40	160
TAP42540	25	40	130
TAP45040	50	40	26



TAP5

ABDECKZAPFEN HIRNHOLZ FICHTE

ART.-NR.	Ø [mm]	H [mm]	Stk.
TAP51020	10	20	500
TAP51220	12	20	500
TAP51420	14	20	500
TAP51520	15	20	500
TAP51620	16	20	500
TAP51820	18	20	250
TAP52020	20	20	250
TAP52220	22	20	250
TAP52420	24	20	250
TAP51240	12	40	450
TAP51640	16	40	250
TAP52040	20	40	160
TAP52540	25	40	130
TAP55040	50	40	26



ANMERKUNGEN:

- Weitere Holzarten wie Kiefer, Eiche, Buche, Erle und Esche sind auf Anfrage erhältlich.
- ^(*) Die anwendbare Feuerwiderstandsdauer muss für jede Verbindung separat nachgewiesen werden.