

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VIN-FIX, Comp. A

UFI: H4S2-K0T6-R00A-4WR3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: ROTHO BLAAS SRL
Street: Via dell'Adige N. 2/1
Place: I-39040 Cortaccia (BZ)
Telephone: +39 0471 81 84 00
e-mail: reach@rothoblaas.com
Internet: www.rothoblaas.com

1.4. Emergency telephone number:

11 (public 24/7 helpline for England (NHS 111), Wales (NHS 111 Wales) and Scotland (NHS 24)), UK NPIS: +44 0344 892 0111 (This number is for use only by healthcare professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Tetramethylene dimethacrylate;
Methacrylic acid, monoester with propane-1,2-diol;
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]
(4-methylphenyl)amino]

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 2 of 16

P362+P364
P501

Take off contaminated clothing and wash it before reuse.
Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
2082-81-7	Tetramethylene dimethacrylate			5 - < 15 %
	218-218-1		01-2119967415-30	
	Skin Sens. 1B; H317			
25013-15-4	Vinyltoluene			1 - < 6 %
	246-562-2		01-2119622074-50	
	Flam. Liq. 3, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2; H226 H315 H400 H411			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			< 2,5 %
	248-666-3		01-2119490226-37	
	Eye Irrit. 2, Skin Sens. 1; H319 H317			
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate			< 0,5 %
	229-934-9		01-2119451093-47	
	Repr. 2, Aquatic Chronic 3; H361d H412			
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]			< 0,5 %
	911-490-9		01-2119979579-10	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H315 H318 H317 H412			
38668-48-3	1,1'-(p-Tolylimino)dipropyl-2-ol			< 0,5 %
	254-075-1		01-2119980937-17	
	Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412			
130-15-4	1,4-naphthoquinone			< 0,05 %
	204-977-6		01-2120760462-57	
	Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H301 H314 H318 H317 H335 H400 H410			

Full text of H and EUH statements: see section 16.

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
2082-81-7	218-218-1	Tetramethylene dimethacrylate	5 - < 15 %
		dermal: LD50 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg	
25013-15-4	246-562-2	Vinyltoluene	1 - < 6 %
		dermal: LD50 = 4585 mg/kg	
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	< 2,5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg	
6846-50-0	229-934-9	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	< 0,5 %
		dermal: LD50 = 18900 mg/kg; oral: LD50 = 3200 mg/kg	
-	911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	< 0,5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 619 mg/kg	
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropyl-2-ol	< 0,5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg	
130-15-4	204-977-6	1,4-naphthoquinone	< 0,05 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: LC50 = 0,046 mg/l (dusts or mists); oral: LD50 = 124 mg/kg M acute; H400: M=10 M chron.; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 4 of 16

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand
Treat the recovered material as prescribed in the section on waste disposal.
Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.
Wear personal protection equipment (refer to section 8).
Avoid contact with skin, eyes and clothes.
When using do not eat, drink or smoke.
Wash hands thoroughly after handling.
Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.
Wash hands thoroughly after handling. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 25°C

7.3. Specific end use(s)

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 5 of 16

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 6 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
2082-81-7	Tetramethylene dimethacrylate			
Worker DNEL, long-term	inhalation	systemic	14,5 mg/m ³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
25013-15-4	Vinyltoluene			
Worker DNEL, long-term	inhalation	systemic	37 mg/m ³	
Worker DNEL, acute	inhalation	systemic	37 mg/m ³	
Worker DNEL, long-term	inhalation	local	37 mg/m ³	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
Worker DNEL, long-term	inhalation	systemic	14,7 mg/m ³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	8,8 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate			
Worker DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	17,62 mg/m ³	
Consumer DNEL, long-term	inhalation	systemic	4,35 mg/m ³	
Consumer DNEL, long-term	oral	systemic	5 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]			
Worker DNEL, long-term	inhalation	systemic	9,8 mg/m ³	
Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m ³	
Consumer DNEL, long-term	oral	systemic	0,83 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day	
38668-48-3	1,1'-(p-Tolylimino)dipropyl-2-ol			
Worker DNEL, long-term	inhalation	systemic	2 mg/m ³	
Worker DNEL, long-term	dermal	systemic	0,6 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,3 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	0,4 mg/m ³	
130-15-4	1,4-naphthoquinone			
Worker DNEL, long-term	inhalation	systemic	0,033 mg/m ³	

Safety Data Sheet

according to UK REACH Regulation

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 7 of 16

PNEC values

CAS No	Substance	
Environmental compartment		Value
2082-81-7	Tetramethylene dimethacrylate	
Freshwater		0,043 mg/l
Marine water		0,004 mg/l
Freshwater sediment		3,12 mg/kg
Marine sediment		0,312 mg/kg
Micro-organisms in sewage treatment plants (STP)		2 mg/l
Soil		0,573 mg/kg
25013-15-4	Vinyltoluene	
Freshwater		0,05 mg/l
Marine water		0,002 mg/l
Freshwater sediment		0,684 mg/kg
Marine sediment		0,684 mg/kg
Soil		0,133 mg/kg
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	
Freshwater		0,904 mg/l
Marine water		0,904 mg/l
Freshwater sediment		6,28 mg/kg
Marine sediment		6,28 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,727 mg/kg
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	
Freshwater		0,014 mg/l
Marine water		0,001 mg/l
Freshwater sediment		5,29 mg/kg
Marine sediment		0,529 mg/kg
Soil		1,05 mg/kg
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	
Freshwater		0,048 mg/l
Marine water		0,005 mg/l
Freshwater sediment		0,12 mg/kg
Marine sediment		0,12 mg/kg
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol	
Freshwater		0,017 mg/l
Marine water		0,0017 mg/l
Freshwater sediment		0,0783 mg/kg
Marine sediment		0,0072 mg/kg
Soil		0,005 mg/kg
130-15-4	1,4-naphthoquinone	
Freshwater		26,1 mg/l
Marine water		2,61 mg/l

Safety Data Sheet

according to UK REACH Regulation

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 8 of 16

Freshwater sediment	321 mg/kg
Marine sediment	32,1 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,172 mg/l
Soil	49 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves
Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: > 0,2 mm
DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)
Colour:	light beige
Odour:	characteristic
Odour threshold:	No data available

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid/liquid:	not determined
---------------	----------------

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 9 of 16

Gas: not applicable

Lower explosion limits: not determined

Upper explosion limits: not determined

Self-ignition temperature

Solid: not determined

Gas: not applicable

Decomposition temperature: not determined

pH-Value: not determined

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: not determined

Density (at 20 °C): 1,72 g/cm³

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

Not oxidising.

Other safety characteristics

Solid content: not determined

Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 11282,6 mg/kg; ATE (inhalation vapour) 265,95 mg/l; ATE (inhalation dust/mist) 36,266 mg/l

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 10 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate				
	oral	LD50 10066 mg/kg	Rat		
	dermal	LD50 > 3000 mg/kg	Rabbit		
25013-15-4	Vinyltoluene				
	dermal	LD50 4585 mg/kg	Rabbit		
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate				
	oral	LD50 3200 mg/kg	Rat		
	dermal	LD50 18900 mg/kg	Guinea pig		
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]				
	oral	LD50 619 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol				
	oral	LD50 > 25 - < 200 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
130-15-4	1,4-naphthoquinone				
	oral	LD50 124 mg/kg	Rat		
	inhalation vapour	ATE 0,5 mg/l			
	inhalation (4 h) dust/mist	LC50 0,046 mg/l	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]; 1,4-naphthoquinone)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 11 of 16

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate					
	Acute algae toxicity	ErC50 mg/l	9,79	72 h		
	Crustacea toxicity	NOEC mg/l	5,09	21 d		
25013-15-4	Vinyltoluene					
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h		
	Acute algae toxicity	ErC50 mg/l	0,319	72 h		
	Acute crustacea toxicity	EC50	9,3 mg/l	48 h	Daphnia magna (Big water flea)	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol					
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 143	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l				
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutryate					
	Algae toxicity	NOEC mg/l	2,25	3 d		
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]					
	Acute fish toxicity	LC50 mg/l	> 100	96 h		
	Acute algae toxicity	ErC50 mg/l	> 100	72 h		
	Acute crustacea toxicity	EC50	48 mg/l	48 h		
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol					
	Acute fish toxicity	LC50	17 mg/l	96 h	Danio rerio (zebrafish)	
	Acute algae toxicity	ErC50	245 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	28,8	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l	57,8	72 d	Desmodesmus subspicatus	OECD 201
130-15-4	1,4-naphthoquinone					
	Acute fish toxicity	LC50 mg/l	0,045	96 h	Oryzias latipes (Ricefish)	
	Acute algae toxicity	ErC50 mg/l	0,42	72 h		
	Acute crustacea toxicity	EC50 mg/l	0,026	48 h		
	Algae toxicity	NOEC mg/l	0,07	3 d		

12.2. Persistence and degradability

The product has not been tested.

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 13 of 16

CAS No	Chemical name	Value	d	Source
	Method			
	Evaluation			
2082-81-7	Tetramethylene dimethacrylate			
	OECD 310	84 %	28	
25013-15-4	Vinyltoluene			
	OECD 310	36,7 %	28	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C	81%	28	
130-15-4	1,4-naphthoquinone			
		39 %	5	

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
25013-15-4	Vinyltoluene	3,35
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	4,91
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	2,17
38668-48-3	1,1'-(p-Tolylimino)dipropyl-2-ol	2,1
130-15-4	1,4-naphthoquinone	1,77

BCF

CAS No	Chemical name	BCF	Species	Source
25013-15-4	Vinyltoluene	100 - 320		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations.

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 14 of 16

- 080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

- 080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

- 150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

- | | |
|--|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Inland waterways transport (ADN)

- | | |
|--|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

- | | |
|--|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Air transport (ICAO-TI/IATA-DGR)

- | | |
|--|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 15 of 16

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)
(SEVESO III):

Additional information

VOC content: 2,8 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service
CLP: Classification, Labeling and Packaging
DMEL: Derived Minimal Effect level
DNEL: Derived No Effect Level
EC50: Effective concentration, 50%
ErC50: EC50 in terms of reduction of growth rate
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
IMDG: International Maritime Code for Dangerous Goods
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
NOEC: No Observed Effect Concentration
OECD: Organisation for Economic Co-operation and Development
PBT: persistent, bioaccumulative and toxic
vPvB: very persistent and very bioaccumulative
PNEC: Predicted No Effect Concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
VOC: Volatile organic compound
Acute Tox. 3: Acute toxicity, Category 3
Acute Tox. 2: Acute toxicity, Category 2
Acute Tox. 4: Acute toxicity, Category 4
Aquatic Acute 1: Acute aquatic hazard, Category 1
Aquatic Chronic 1: Long-term aquatic hazard, Category 1
Aquatic Chronic 3: Long-term aquatic hazard, Category 3
Asp. Tox. 1: Aspiration hazard, Category 1
Eye Dam. 1: Serious eye damage/eye irritation, Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
Flam. Liq. 3: Flammable liquid, Category 3
Repr. 2: Reproductive toxicity, Category 2
Skin Corr. 1C: Skin corrosion/irritation, Category 1C

VIN-FIX, Comp. A

Revision date: 14.10.2022

Page 16 of 16

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2
 Skin Sens. 1A: Skin sensitization, Category 1A
 Skin Sens. 1B: Skin sensitization, Category 1B
 STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
 H300 Fatal if swallowed.
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H335 May cause respiratory irritation.
 H361d Suspected of damaging the unborn child.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VIN-FIX, Comp. B

UFI: D6S2-30GM-100U-T8A5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: ROTHO BLAAS SRL
Street: Via dell'Adige N. 2/1
Place: I-39040 Cortaccia (BZ)
Telephone: +39 0471 81 84 00
e-mail: reach@rothoblaas.com
Internet: www.rothoblaas.com

1.4. Emergency telephone number:

11 (public 24/7 helpline for England (NHS 111), Wales (NHS 111 Wales) and Scotland (NHS 24)), UK NPIS: +44 0344 892 0111 (This number is for use only by healthcare professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Irrit. 2; H319
Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Dibenzoyl peroxide

Signal word: Warning

Pictograms:



Hazard statements

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing vapours.
P280 Wear protective gloves and eye/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 2 of 10

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
94-36-0	Dibenzoyl peroxide			5 - < 15 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 15 %
	oral: LD50 = > 5000 mg/kg M acute; H400: M=10 M chron.; H410: M=10		

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to UK REACH Regulation

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 3 of 10

Suitable extinguishing media

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand
Treat the recovered material as prescribed in the section on waste disposal.
Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.
Wear personal protection equipment (refer to section 8).
Avoid contact with skin, eyes and clothes.
When using do not eat, drink or smoke.
Wash hands thoroughly after handling.
Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.
Wash hands thoroughly after handling. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 4 of 10

Store in a place accessible by authorized persons only.
Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong
Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.
storage temperature: 5 - 25°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m³

PNEC values

CAS No	Substance	Value
	Environmental compartment	
94-36-0	Dibenzoyl peroxide	
Freshwater		0,00002 mg/l
Marine water		0,000002 mg/l
Freshwater sediment		0,013 mg/kg
Marine sediment		0,001 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 5 of 10

must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)
Colour:	black
Odour:	characteristic
Odour threshold:	No data available

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid/liquid:	not determined
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Self-ignition temperature

Solid:	not determined
Gas:	not applicable
Decomposition temperature:	not determined
pH-Value:	not determined

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
-------------------	--

Solubility in other solvents

not determined	
Partition coefficient n-octanol/water:	not determined

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 6 of 10

Vapour pressure: not determined
Density (at 20 °C): 1,59 g/cm³
Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
Not oxidising.
Available oxygen content < 1%
no classification

Other safety characteristics

Solid content: not determined
Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Benzoic acid
Benzene
Biphenyl

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

Irritation and corrosivity

Causes serious eye irritation.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 7 of 10

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus)

IC10: (0 - 72 h) = 30 mg/l

IC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna)

EC0/NOEC (48h) = 100 mg/l

EC50 (48h) = >500 mg/l

EC100 (48h) = >>500 mg/l

OECD 203 (Danio rerio)

LC0/NOEC (96 h) : 250 mg/l

LC50 (96 h) : > 500 mg/l

LC100 (96 h) : >> 500 mg/l

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide					
	Acute fish toxicity	LC50 mg/l	0,0602	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	0,0711	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,11	48 h	Daphnia magna (Big water flea)	OECD 202
	Algae toxicity	NOEC mg/l	0,02	3 d	Pseudokirchneriella subcapitata	OECD 201
	Crustacea toxicity	NOEC mg/l	0,001	21 d	Daphnia magna (Big water flea)	OECD 211
	Acute bacteria toxicity	(EC50	35 mg/l)	0,5 h		OECD 209

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 8 of 10

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations.

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 9 of 10

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)
(SEVESO III):

Additional information

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

VIN-FIX, Comp. B

Revision date: 14.10.2022

Page 10 of 10

EC50: Effective concentration, 50%
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
 ICAO: International Civil Aviation Organization
 IC50: Inhibitory concentration, 50%
 IMDG: International Maritime Code for Dangerous Goods
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 NOEC: No Observed Effect Concentration
 OECD: Organisation for Economic Co-operation and Development
 PBT: persistent, bioaccumulative and toxic
 vPvB: very persistent and very bioaccumulative
 PNEC: Predicted No Effect Concentration
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
 VOC: Volatile organic compound
 Aquatic Acute 1: Acute aquatic hazard, Category 1
 Aquatic Chronic 1: Long-term aquatic hazard, Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
 Skin Sens. 1: Skin sensitization, Category 1
 Org. Perox. B: Organic Peroxides, Type B

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H241 Heating may cause a fire or explosion.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)