

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: BYTS (UFI APC0-S095-W004-MTJT)
Product name: BYTUM SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Solvent-based bituminous primer for construction in spray packaging

Identified Uses	Industrial	Professional	Consumer
Primer spray	-	ERC: 4. PROC: 11. PC: 9a. LCS: C.	ERC: 4. PROC: 11. PC: 9a. LCS: C.

Uses Advised Against

Dispersive use in non-ventilated rooms

1.3. Details of the supplier of the safety data sheet

Name: ROTHO BLAAS SRL
Full address: Via dell'Adige N. 2/1
District and Country: I-39040 Cortaccia (BZ) Italia
Tel. +39 0471 81 84 00
Fax +39 0471 81 84 84
e-mail address of the competent person responsible for the Safety Data Sheet: reach@rothoblaas.com

1.4. Emergency telephone number

For urgent inquiries refer to: National Poisons Information Service (NPIS) - Email: director.birmingham.unit@npis.org

Members of the public seeking specific information on poisons should contact:
England and Wales: NHS 111 - dial 111;
Scotland: NHS 24 - dial 111;
N Ireland: Contact your local GP or pharmacist during normal hours; click here (www.gpoutofhours.hscni.net/) for GP services Out-of-Hours;
Republic of Ireland: 01 809 2166

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
Skin irritation, category 2	H229	Pressurised container: may burst if heated.
Specific target organ toxicity - single exposure, category 3	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, chronic toxicity, category 2	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.

SECTION 2. Hazards identification ... / >>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P264	Wash hands thoroughly with soap and water after use.
P273	Avoid release to the environment.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P102	Keep out of reach of children.

Contains: SOLVENT NAPHTA (PETROLEUM), LIGHT AROM
HEPTANE
ETHYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
SOLVENT NAPHTA (PETROLEUM), LIGHT AROM		
CAS	25 $\leq$ x < 30	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066
EC	918-668-5	
INDEX		
Reg. no.	01-2119455851-35	
HEPTANE		
CAS	142-82-5 15 $\leq$ x < 20	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1, Classification note/notes according to Annex VI to the CLP Regulation: C
EC	205-563-8	
INDEX	601-008-00-2	
Reg. no.	01-2119475515-33	

SECTION 3. Composition/information on ingredients ... / >>

DIMETHYL ETHER

CAS 115-10-6 $9 \leq x < 9,9$ **Flam. Gas 1A H220, Press. Gas H280**
EC 204-065-8
INDEX 603-019-00-8
Reg. no. 01-2119472128-37

CARBON DIOXIDE

CAS 124-38-9 $1 \leq x < 3$ **Substance with a community workplace exposure limit.**
EC 204-696-9
INDEX

ETHYL ACETATE

CAS 141-78-6 $1 \leq x < 3$ **Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066**
EC 205-500-4
INDEX 607-022-00-5
Reg. no. 01-2119475103-46

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.
Percentage of propellants: 11,00 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany): 2B

7.3. Specific end use(s)

See the exposure scenarios attached to this safety datasheet.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL- OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 10/2018
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM–SZCSM együ, TTes rendelet módosításáról.
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de

SECTION 8. Exposure controls/personal protection ... / >>

PRT	Portugal	implementatie van Richtlijn 2017/164 in Bijlage XIII
POL	Polska	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
SWE	Sverige	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVK	Slovensko	Hygieniska gränsvärden, AFS 2018:1
SVN	Slovenija	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov
TUR	Türkiye	Uradni list Republike Slovenije 20.12.2019 - Uradnem listu RS št. 78/19 -PRAVILNIK o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
GBR	United Kingdom	12.08.2013 Tarihli, 28733 Sayılı, Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik
EU	OEL EU	EH40/2005 Workplace exposure limits (Third edition, published 2018)
	TLV-ACGIH	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
		ACGIH 2020

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	mg/m3	
		ppm	ppm	
TLV-ACGIH		100	20	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				11				
				mg/kg/d				
Inhalation				32				150
				mg/m3				mg/m3
Skin				11				25
				mg/kg/d				mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

HEPTANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1600				
TLV	CZE	1000	240	2000	480	
MAK	DEU	2100	500	2100	500	
TLV	DNK	820	200			E
VLA	ESP	2085	500			Como n-Eptano
VLEP	FRA	1668	400	2085	500	
TLV	GRC	2000	500	2000	500	
AK	HUN	2000				
GVI/KGVI	HRV	2085	500			SKIN
VLEP	ITA	2085	500			
TLV	NOR	800	200			
TGG	NLD	1200		1600		
VLE	PRT	2085	500			
NDS/NDSch	POL	1200		2000		
TLV	ROU	2085	500			
NGV/KGV	SWE	800	200	1200 (C)	300 (C)	
NPEL	SVK	2085	500			
MV	SVN	2085	500	2085	500	
ESD	TUR	2085	500			
WEL	GBR	2085	500			
OEL	EU	2085	500			
TLV-ACGIH		1639	400	2049	500	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				149 mg/kg bw/d				
Inhalation				447 mg/m3				2085 mg/m3
Skin				149 mg/kg bw/d				300 mg/kg bw/d

DIMETHYL ETHER

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		1920	1000			

SECTION 8. Exposure controls/personal protection ... / >>

CARBON DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	9000	5000			
TLV	CZE	9000	4923	45000	24615	
AGW	DEU	9100	5000	18200	10000	
MAK	DEU	9100	5000	18200	10000	
TLV	DNK	9000	5000			E
VLA	ESP	9150	5000			
VLEP	FRA	9000	5000			
HTP	FIN	9100	5000			
TLV	GRC	9000	5000	54000	5000	
AK	HUN	9000				
GVI/KGVI	HRV	9000	5000			
VLEP	ITA	9000	5000			
TLV	NOR	9000	5000			
TGG	NLD	9000				
VLE	PRT	9000	5000			
NDS/NDSch	POL	9000		27000		
TLV	ROU	9000	5000			
NGV/KGV	SWE	9000	5000	18000 (C)	10000 (C)	
NPEL	SVK	9000	5000			
MV	SVN	9000	5000			
ESD	TUR	9000	5000			
WEL	GBR	9150	5000	27400	15000	
OEL	EU	9000	5000			
TLV-ACGIH		9000	5000	54000	30000	

SECTION 8. Exposure controls/personal protection ... / >>

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	734	200	1468	400	
TLV	CZE	700	191,1	900	245,7	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
TLV	DNK	540	150			E
VLA	ESP	734	200	1468	400	
VLEP	FRA	734	200	1468	400	
HTP	FIN	730	200	1470	400	
TLV	GRC	734	200	1468	400	
AK	HUN	734		1468		
GVI/KGVI	HRV	734	200	1468	400	
TLV	NOR	734	200			
TGG	NLD	734		1468		
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	400	111	500	139	
NGV/KGV	SWE	550	150	1100	300	
NPEL	SVK	734	200	1468	400	
MV	SVN	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,24	mg/l
Normal value in marine water	0,024	mg/l
Normal value for fresh water sediment	1,15	mg/kg
Normal value for marine water sediment	0,0115	mg/kg
Normal value of STP microorganisms	650	mg/l
Normal value for the terrestrial compartment	0,148	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,5 mg/kg bw/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin				37 mg/kg bw/d				63 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

When choosing risk management measures and operating conditions, consult the exposure scenarios attached.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In cases of potential contact, use chemical resistant gloves such as neoprene, PVC, nitrile with a minimum thickness of 0.38 mm, or equivalent protective barrier material with high level performance. For conditions of use in continuous contact, a minimum permeability time of 480 minutes in accordance with the CEN standard EN 420, EN 374. Working conditions can significantly affect the suitability and durability of the gloves. Replace gloves at the first signs of wear.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX

SECTION 8. Exposure controls/personal protection ... / >>

filter combined with a type P filter should be worn (see standard EN 14387).Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

For information on controlling environmental exposure, see the exposure scenarios attached to this safety datasheet.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	Spray	
Colour	black	
Odour	characteristic	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not applicable	
Boiling range	Not available	
Flash point	Not applicable	
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	Not available	
Solubility	Not available	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	Not available	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

VOC (Directive 2010/75/EC) :	46,00 %
VOC (volatile carbon) :	38,28 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

SECTION 10. Stability and reactivity ... / >>

10.4. Conditions to avoid

Avoid overheating.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM

LD50 (Oral)

3492 mg/kg Rat

LD50 (Dermal)

> 3160 mg/kg Rabbit

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation
May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM

LC50 - for Fish	9,2 mg/l/96h Fish
EC50 - for Crustacea	3,2 mg/l/48h Dafnia

HEPTANE

LC50 - for Fish	375 mg/l/96h Tilapia mossambica
EC50 - for Crustacea	82,5 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	1,5 mg/l/72h Algae

12.2. Persistence and degradability

HEPTANE

Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

ETHYL ACETATE

Solubility in water	> 10000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

HEPTANE

Partition coefficient: n-octanol/water	4,5
BCF	552

ETHYL ACETATE

Partition coefficient: n-octanol/water	0,68
BCF	30

12.4. Mobility in soil

HEPTANE

Partition coefficient: soil/water	2,38
-----------------------------------	------

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

SECTION 12. Ecological information ... / >>

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS

IMDG: AEROSOLS (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM)

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: Environmentally Hazardous



For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

SECTION 14. Transport information ... / >>

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: -	Limited Quantities: 1 L	
IATA:	EMS: F-D, S-U	Maximum quantity: 150 Kg	Packaging instructions: 203
	Cargo:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Pass.:		
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

SOLVENT NAPHTA (PETROLEUM), LIGHT AROM

HEPTANE

ETHYL ACETATE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas	Pressurised gas
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2

SECTION 16. Other information ... / >>

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Use descriptor system:

ERC	4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
LCS	C	Consumer use
PC	9a	Coatings and paints, thinners, paint removers
PROC	11	Non industrial spraying

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)

SECTION 16. Other information ... / >>

15. Regulation (EU) 2018/1480 (XIII Atp. CLP) 16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 08.

Exposure Scenarios

Substance SOLVENT NAPHTA (PETROLEUM), LIGHT AROM
Scenario Title SOLVENT NAPHTA (PETROLEUM), LIGHT AROM
Revision nr. 1
File EN_918_668_5_1.pdf

Substance HEPTANE
Scenario Title HEPTANE
Revision nr. 1
File EN_205_563_8_1.pdf

Substance ETHYL ACETATE
Scenario Title ETHYL ACETATE
Revision nr. 1
File EN_205_500_4_1.pdf