



Make it easy.

Safety data sheet according to 1907/2006/EC, Article 31

Page 1/14

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** UNIVERSAL FOAM
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Assembly foam
- **Application of the substance / the mixture** Construction chemicals
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
ROTHO BLAAS SRL
Via dell'Adige N. 2/1 I-39040,
Cortaccia (BZ)
Tel. +39 0471 81 84 00
E-mail reach@rothoblaas.com
- **Further information obtainable from:** reach@rothoblaas.com
- **1.4 Emergency telephone number:** European emergency number: 112 (24h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2 H351 Suspected of causing cancer.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
Lact. H362 May cause harm to breast-fed children.
Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

· **Additional information:**

Classification of the preparation with attributed H413 phrase, taking into account the content C14-C17 chlorinated alkanes, was made on the basis of acute toxicology tests; FEICA Position Paper 17.03.2014.

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 1)

2.2 Label elements**· Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labelling:**diphenylmethanediisocyanate, isomers and homologues
chlorinated paraffins, C14-17**· Hazard statements**

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H362 May cause harm to breast-fed children.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H413 May cause long lasting harmful effects to aquatic life.

· Precautionary statements

P102 Keep out of reach of children.
P260 Do not breathe gas.
P263 Avoid contact during pregnancy and while nursing.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information at: www.feica.eu/PUinfo
Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Do not spray on an open flame or other ignition source.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 2)

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties

CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate

List II

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	30 - 60%
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chlorisopropyl)-phosphate ⚠ Acute Tox. 4, H302	< 25%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33-xxxx	chlorinated paraffins, C14-17 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10); Lact., H362, EUH066	< 20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 86675-46-9 Reg.nr.: 01-2119972940-30-xxxx	halogenated polyetherpolyol ⚠ Acute Tox. 4, H302	< 15%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 10%
CAS: 6425-39-4 Reg.nr.: 01-2119969278-20-0001	2,2-dimorpholinodiethylether ⚠ Eye Irrit. 2, H319	< 2%

SVHC

CAS: 85535-85-9 chlorinated paraffins, C14-17

Additional information: For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 4)



Make it easy.

Safety data sheet according to 1907/2006/EC, Article 31

Page 4/14

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 3)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· **After skin contact:**

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

Carbon dioxide.

Fire-extinguishing powder.

Foam.

Water spray.

Use fire extinguishing methods suitable to surrounding conditions.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet.

· 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· **Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

· **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective clothing.

Do not breathe gas / fumes / vapour / spray.

Ensure adequate ventilation.

· 6.2 Environmental precautions: Do not allow to enter sewers / surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to item 13.

(Contd. on page 5)



Make it easy.

Safety data sheet according to 1907/2006/EC, Article 31

Page 5/14

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

Ensure adequate ventilation.

(Contd. of page 4)

· **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care.
Do not pierce or burn even after use. Use only as directed on the label.
Do not mix with any other chemical products.
Ensure good ventilation / exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

This product is subject to regulations governing the storage of highly flammable aerosol products.
Storage rooms should be equipped with heat and smoke detectors.
Electrical equipment should be explosion-proof.
Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Do not store together with acids.
Do not store together with alkalis (caustic solutions).
Store away from reducing agents.
Store away from oxidising agents.
Store away from foodstuffs.
Store away from plastic, rubber, aluminum, light-metals.

· Further information about storage conditions:

Store receptacle in a well ventilated area.
Store in vertical position in closed original containers.
Store at temperature from +5°C to +30°C.
Protect from frost.
Store under lock and key and out of the reach of children.
Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

(Contd. on page 6)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 5)

CAS: 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

CAS: 106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

· DNELs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	DNEL	20 mg/kg/Tag (General population, consumers)
Dermal	DNEL	0.05 mg/kg/Tag (General population, consumers)
Inhalative	DNEL	0.05 mg/m ³ (General population, consumers) 0.05 mg/m ³ (Workers)

CAS: 85535-85-9 chlorinated paraffins, C14-17

Oral	DNEL	0.115 mg/kg/Tag (General population, consumers)
Dermal	DNEL	5.75 mg/kg/Tag (General population, consumers) 11.5 mg/kg/Tag (Workers)
Inhalative	DNEL	0.4 mg/m ³ (General population, consumers) 1.6 mg/m ³ (Workers)

CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate

Oral	DNEL	0.52 mg/kg/Tag (General population, consumers) 1.04 mg/kg/Tag (Workers)
Dermal	DNEL	4 mg/kg/Tag (General population, consumers) 2.08 mg/kg/Tag (Workers)
Inhalative	DNEL	11.2 mg/m ³ (General population, consumers) 5.82 mg/m ³ (Workers)

CAS: 115-10-6 dimethyl ether

Inhalative	DNEL	471 mg/m ³ (General population, consumers) 1,894 mg/m ³ (Workers)
------------	------	--

CAS: 86675-46-9 halogenated polyetherpolyol

Oral	DNEL	0.44 mg/kg/Tag (General population, consumers)
Dermal	DNEL	0.44 mg/kg/Tag (General population, consumers) 0.87 mg/kg/Tag (Workers)
Inhalative	DNEL	1.5 mg/m ³ (General population, consumers) 6 mg/m ³ (Workers)

CAS: 6425-39-4 2,2-dimorpholinodiethylether

Oral	DNEL	0.5 mg/kg/Tag (General population, consumers)
Dermal	DNEL	1 mg/kg/Tag (Workers)
Inhalative	DNEL	1.8 mg/m ³ (General population, consumers) 7.28 mg/m ³ (Workers)

· PNECs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(soil)	1 mg/kg

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 6)

CAS: 85535-85-9 chlorinated paraffins, C14-17	
(freshwater)	1 mg/l
(sea water)	0.2 mg/l
(freshwater sediments)	13 mg/kg
(sea water sediments)	2.6 mg/kg
(soil)	20 mg/kg
CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate	
(freshwater sediments)	13.4 mg/kg
(sea water sediments)	1.34 mg/kg
(soil)	1.7 mg/kg
CAS: 115-10-6 dimethyl ether	
(freshwater)	0.155 mg/l (Aquatic Organisms)
(sea water)	0.016 mg/l (Aquatic Organisms)
(freshwater sediments)	0.681 mg/kg (Aquatic Organisms)
(sea water sediments)	0.069 mg/kg (Aquatic Organisms)
(soil)	0.045 mg/kg (Terrestrial Organism)
CAS: 86675-46-9 halogenated polyetherpolyol	
(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(freshwater sediments)	37.5 mg/kg
(sea water sediments)	3.75 mg/kg
(soil)	6.92 mg/kg
CAS: 6425-39-4 2,2-dimorpholinodiethylether	
(freshwater)	0.1 mg/l (Aquatic Organisms)
(sea water)	0.01 mg/l (Aquatic Organisms)
(freshwater sediments)	8.2 mg/kg (Aquatic Organisms)
(sea water sediments)	0.82 mg/kg (Aquatic Organisms)
(soil)	1.58 mg/kg (Terrestrial Organism)

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**



Protective gloves

EN 374

(Contd. on page 8)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 7)

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Polyethylene gloves.

Recommended thickness of the material: ≥ 0.02 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialShort-term exposure ≥ 10 min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Tightly sealed goggles

EN 166

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information**

· Colour:	Different according to colouring
· Odour:	Characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol
· Lower and upper explosion limit	
· Lower:	1.5 Vol %
· Upper:	11.0 Vol %
· Flash point:	< 0 °C
· Auto-ignition temperature:	$> +350$ °C (propellant)
· Solubility	
· water:	Insoluble Reacts with water
· Vapour pressure:	> 500 kPa (in the container) $< 1 \cdot 10^{-5}$ mmHg w 25°C (MDI)
· Density and/or relative density	
· Density at 20 °C:	≤ 1.3 (PMDI) g/cm ³

9.2 Other information

· Appearance:	
· Form:	Rapidly curing foam dispensed by gaseous propellant from an aerosol container

(Contd. on page 9)



Safety data sheet according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 8)

· Important information on protection of health and environment, and on safety.**· Explosive properties:** Heating may cause an explosion.**· Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	
Extremely flammable aerosol.	
Pressurised container: May burst if heated.	
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Strongly reacts with water and other substances containing an active hydrogen atom.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
Harmful if inhaled.

(Contd. on page 10)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 9)

LD/LC50 values relevant for classification:**CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Oral	LD50	>10,000 mg/kg (rat) (OECD401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)
Inhalative	LC50/4h	1.5 mg/l (ATE)

CAS: 85535-85-9 chlorinated paraffins, C14-17

Dermal	LD50	4,000 mg/kg (rat)
Inhalative	LC50	>3,300 mg/l (rat)

CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate

Oral	LD50	1,017 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

CAS: 86675-46-9 halogenated polyetherpolyol

Oral	LD50	917 mg/kg (rat)
------	------	-----------------

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity**

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate

List II

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:****CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

EC50	1,640 mg/l (algae)
	>1,000 mg/l (daphnia) (OECD202)
	>100 mg/l (Sedimentation) (OECD209)
LC50	>1,000 mg/l (fish) (OECD)

CAS: 85535-85-9 chlorinated paraffins, C14-17

EC50	>3.2 mg/l (algae) (OECD 201)
	0.006 mg/l (daphnia)

(Contd. on page 11)



Make it easy.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 10)

LC50 >5,000 mg/l (fish)

- **12.2 Persistence and degradability** Not biodegradable.
- **12.3 Bioaccumulative potential** Does not accumulate in organisms.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Dispose of in a safe manner in accordance with local / national regulations.
Do not allow to enter surface or ground water.
Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

· **European waste catalogue**

15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers
-----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|----------|
| · 14.1 UN number or ID number
· ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name
· ADR, IMDG, IATA | AEROSOLS |

· **14.3 Transport hazard class(es)**· **ADR**

- **Class** 2 5F Gases.

(Contd. on page 12)



Make it easy.

Page 12/14

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 11)

· Label	2.1
· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· 14.4 Packing group	-
· 14.5 Environmental hazards:	
· Marine pollutant:	No.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Remarks:	Exemption from ADR provisions by LQ principal (rule 3.4) - Inner packaging, max. 1 liter in capacity; outer packaging – max. gross weight of 30kg. - Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film – max. gross weight of 20kg.
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
1907/2006/CE Regulation, REACH
1272/2008/CE Regulation, CLP
2020/878/UE Regulation
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 56, 74
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.

(Contd. on page 13)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Make it easy.

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 12)

· REGULATION (EU) 2019/1148**· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Other regulations, limitations and prohibitive regulations**· Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 85535-85-9 | chlorinated paraffins, C14-17

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 14)



Make it easy.

Safety data sheet according to 1907/2006/EC, Article 31

Page 14/14

Printing date 01.09.2021

Version number 1

Revision: 22.02.2021

Trade name: UNIVERSAL FOAM

(Contd. of page 13)

Carc. 2: Carcinogenicity – Category 2
Lact.: Reproductive toxicity – effects on or via lactation
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

GB