

**Safety Data Sheet**

according to UK REACH Regulation

**beko Holzgleit**

Revision: 04.06.2025

Product code: 299 512/503

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Holzgleit

UFI: 5DM7-Y422-JS80-U3US

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Mittel für die Holzverarbeitung (Gleitmittel) zur gewerblichen Verwendung

**1.3. Details of the supplier of the safety data sheet**

Company name: beko GmbH

Street: Rappenfeldstr. 5

Place: DE-86653 Monheim

Telephone: +49 (0) 9091/90898-0

Telefax: +49 (0) 9091/90898-29

E-mail: info@beko-group.com

**1.4. Emergency telephone number:**

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 3; H226

STOT SE 3; H336

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten  
weisses Mineralöl

Signal word: Danger

Pictograms:

**Hazard statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

**Safety Data Sheet**

according to UK REACH Regulation

**beko Holzgleit**

Revision: 04.06.2025

Product code: 299 512/503

Page 2 of 10

**Special labelling of certain mixtures**

EUH066

Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

| CAS No    | Chemical name                                                              |          |                  | Quantity    |
|-----------|----------------------------------------------------------------------------|----------|------------------|-------------|
|           | EC No                                                                      | Index No | REACH No         |             |
|           | Classification (GB CLP Regulation)                                         |          |                  |             |
|           | Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten |          |                  | 75 - < 95 % |
|           | 919-857-5                                                                  |          | 01-2119463258-33 |             |
|           | Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066                |          |                  |             |
| 8042-47-5 | weisses Mineralöl                                                          |          |                  | 20 - < 25 % |
|           | 232-455-8                                                                  |          | 01-2119487078-27 |             |
|           | Asp. Tox. 1; H304                                                          |          |                  |             |

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No    | EC No                                                                                         | Chemical name                                                              | Quantity    |
|-----------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|-------------|
|           | Specific Conc. Limits, M-factors and ATE                                                      |                                                                            |             |
|           | 919-857-5                                                                                     | Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten | 75 - < 95 % |
|           | inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg |                                                                            |             |
| 8042-47-5 | 232-455-8                                                                                     | weisses Mineralöl                                                          | 20 - < 25 % |
|           | inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg |                                                                            |             |

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.

**After inhalation**

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

**After contact with skin**

Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

**After ingestion**

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Medical treatment necessary.

**4.2. Most important symptoms and effects, both acute and delayed**

May cause drowsiness or dizziness. Headache

Ingestion causes nausea, weakness and central nervous system effects.

**4.3. Indication of any immediate medical attention and special treatment needed**

# Safety Data Sheet

according to UK REACH Regulation

**beko Holzgleit**

Revision: 04.06.2025

Product code: 299 512/503

Page 3 of 10

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air.

Hazardous combustion products: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>)**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Use personal protection equipment.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Special danger of slipping by leaking/spilling product. Remove all sources of ignition. Provide adequate ventilation.

**For non-emergency personnel**

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

**For emergency responders**

Use personal protection equipment.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Vapours can form explosive mixtures with air. (5.2)

**6.3. Methods and material for containment and cleaning up****For containment**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Wipe up with absorbent material (eg. cloth, fleece).

**Other information**

Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

# Safety Data Sheet

according to UK REACH Regulation

## beko Holzgleit

Revision: 04.06.2025

Product code: 299 512/503

Page 4 of 10

### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

### 7.3. Specific end use(s)

Lubrificant nella lavorazione del legno  
Gleitmittel in der Holzverarbeitung

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### DNEL/DMEL values

| CAS No                   | Substance                                                                  |                |          |                  |
|--------------------------|----------------------------------------------------------------------------|----------------|----------|------------------|
| DNEL type                |                                                                            | Exposure route | Effect   | Value            |
|                          | Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten |                |          |                  |
| Consumer DNEL, long-term |                                                                            | oral           | systemic | 300 mg/kg bw/day |
| Worker DNEL, long-term   |                                                                            | dermal         | systemic | 300 mg/kg bw/day |
| Worker DNEL, long-term   |                                                                            | inhalation     | systemic | 1500 mg/m³       |
| Consumer DNEL, long-term |                                                                            | inhalation     | systemic | 900 mg/m³        |
| Consumer DNEL, long-term |                                                                            | dermal         | systemic | 300 mg/kg bw/day |

#### Additional advice on limit values

To date, no national critical limit values exist.

### 8.2. Exposure controls



#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended material:

NBR (Nitrile rubber) (0,4 mm), Breakthrough time: >480 min

# Safety Data Sheet

according to UK REACH Regulation

## beko Holzgleit

Revision: 04.06.2025

Product code: 299 512/503

Page 5 of 10

### Skin protection

Wear suitable protective clothing.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                                           |                                                                                                  |                    |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------|
| Physical state:                                           | Liquid                                                                                           |                    |
| Colour:                                                   | colourless                                                                                       |                    |
| Odour:                                                    | characteristic (Solvents)                                                                        |                    |
| Odour threshold:                                          | not determined                                                                                   |                    |
|                                                           |                                                                                                  | <b>Test method</b> |
| Melting point/freezing point:                             | <-50 °C                                                                                          |                    |
| Boiling point or initial boiling point and boiling range: | 155 °C                                                                                           |                    |
| Flammability:                                             | not applicable                                                                                   |                    |
|                                                           | not applicable                                                                                   |                    |
| Lower explosion limits:                                   | 0,7 g/m <sup>3</sup>                                                                             |                    |
| Upper explosion limits:                                   | 6 g/m <sup>3</sup>                                                                               |                    |
| Flash point:                                              | 39 °C                                                                                            | ASTM D 3278        |
| Auto-ignition temperature:                                | >200 °C                                                                                          |                    |
| Decomposition temperature:                                | not determined                                                                                   |                    |
| pH-Value:                                                 | not applicable                                                                                   |                    |
| Viscosity / kinematic:<br>(at 20 °C)                      | 20,2 mm <sup>2</sup> /s                                                                          |                    |
| Water solubility:                                         | The study does not need to be conducted because the substance is known to be insoluble in water. |                    |
| Solubility in other solvents                              |                                                                                                  |                    |
| not determined                                            |                                                                                                  |                    |
| Partition coefficient n-octanol/water:                    | not determined                                                                                   |                    |
| Vapour pressure:<br>(at 20 °C)                            | 3 hPa                                                                                            |                    |
| Density (at 20 °C):                                       | 0,79 g/cm <sup>3</sup>                                                                           |                    |
| Relative vapour density:                                  | not determined                                                                                   |                    |
| Particle characteristics:                                 | not relevant                                                                                     |                    |

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

Vapours can form explosive mixtures with air.

##### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

##### Oxidizing properties

Not oxidising.

#### Other safety characteristics

##### Evaporation rate:

not determined

##### Solvent content:

VOC value (Section 15: Regulatory Information (non-mandatory))

Viscosity / dynamic:  
(at 20 °C)

16 mPa·s ISO 2555

**Safety Data Sheet**

according to UK REACH Regulation

**beko Holzgleit**

Revision: 04.06.2025

Product code: 299 512/503

Page 6 of 10

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable, Ignition hazard.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

**10.5. Incompatible materials**

Oxidising agent

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

Hazardous combustion products: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>)**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

| CAS No    | Chemical name                                                              |               |         |        |                   |
|-----------|----------------------------------------------------------------------------|---------------|---------|--------|-------------------|
|           | Exposure route                                                             | Dose          | Species | Source | Method            |
|           | Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten |               |         |        |                   |
|           | oral                                                                       | LD50<br>mg/kg | >5000   | Rat    | SDB Scharrsol D40 |
|           | dermal                                                                     | LD50<br>mg/kg | >2000   | Rat    | SDB Scharrsol D40 |
|           | inhalation vapour                                                          | LC50<br>mg/l  | >5000   | Rat    | ECHA<br>OECD 403  |
| 8042-47-5 | weisses Mineralöl                                                          |               |         |        |                   |
|           | oral                                                                       | LD50<br>mg/kg | >5000   | Rat    |                   |
|           | dermal                                                                     | LD50<br>mg/kg | >2000   | Rabbit |                   |
|           | inhalation (4 h) vapour                                                    | LC50<br>mg/l  | >5000   | Rat    |                   |

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

**Safety Data Sheet**

according to UK REACH Regulation

**beko Holzgleit**

Revision: 04.06.2025

Product code: 299 512/503

Page 7 of 10

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, &lt;2% Aromaten)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

| CAS No    | Chemical name                                                              |               |           |         |                                        |         |
|-----------|----------------------------------------------------------------------------|---------------|-----------|---------|----------------------------------------|---------|
|           | Aquatic toxicity                                                           | Dose          | [h]   [d] | Species | Source                                 | Method  |
|           | Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten |               |           |         |                                        |         |
|           | Acute fish toxicity                                                        | LC50<br>mg/l  | >1000     | 96 h    | Oncorhynchus mykiss<br>(Rainbow trout) |         |
|           | Acute algae toxicity                                                       | ErC50<br>mg/l | >1000     |         | Pseudokirchneriella<br>subcapitata     |         |
|           | Acute crustacea toxicity                                                   | EC50<br>mg/l  | >1000     | 48 h    |                                        |         |
| 8042-47-5 | weisses Mineralöl                                                          |               |           |         |                                        |         |
|           | Acute fish toxicity                                                        | LC50<br>mg/l  | >1000     | 96 h    | Leuciscus idus<br>(golden orfe)        |         |
|           | Acute crustacea toxicity                                                   | EC50<br>mg/l  | >100      | 48 h    | Daphnia magna (Big<br>water flea)      |         |
|           | Algae toxicity                                                             | NOEC<br>mg/l  | >100      | 3 d     | Pseudokirchneriella<br>subcapitata     | OECD201 |

**12.2. Persistence and degradability**

The product has not been tested.

| CAS No    | Chemical name                                                              |       |    |                   |
|-----------|----------------------------------------------------------------------------|-------|----|-------------------|
|           | Method                                                                     | Value | d  | Source            |
|           | Evaluation                                                                 |       |    |                   |
|           | Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten |       |    |                   |
|           | Kohlendioxidbildung                                                        | 0%    | 3  | SDB Scharrsol D40 |
|           | Sauerstoffverbrauch                                                        | 10 %  | 5  | SDB Scharrsol D40 |
| 8042-47-5 | weisses Mineralöl                                                          |       |    |                   |
|           | OECD 301 F                                                                 | 31,3  | 28 |                   |

**12.3. Bioaccumulative potential**

# Safety Data Sheet

according to UK REACH Regulation

## beko Holzgleit

Revision: 04.06.2025

Product code: 299 512/503

Page 8 of 10

The product has not been tested.

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### Further information

Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### List of Wastes Code - residues/unused products

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); Solvents; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

|                                          |                              |
|------------------------------------------|------------------------------|
| <b>14.1. UN number or ID number:</b>     | UN 3295                      |
| <b>14.2. UN proper shipping name:</b>    | HYDROCARBONS, LIQUID, N.O.S. |
| <b>14.3. Transport hazard class(es):</b> | 3                            |
| <b>14.4. Packing group:</b>              | III                          |
| Hazard label:                            | 3                            |



|                          |     |
|--------------------------|-----|
| Classification code:     | F1  |
| Limited quantity:        | 5 L |
| Excepted quantity:       | E1  |
| Transport category:      | 3   |
| Hazard No:               | 30  |
| Tunnel restriction code: | D/E |

### Inland waterways transport (ADN)

|                                       |                              |
|---------------------------------------|------------------------------|
| <b>14.1. UN number or ID number:</b>  | UN 3295                      |
| <b>14.2. UN proper shipping name:</b> | HYDROCARBONS, LIQUID, N.O.S. |

# Safety Data Sheet

according to UK REACH Regulation

## beko Holzgleit

Revision: 04.06.2025

Product code: 299 512/503

Page 9 of 10

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** III

Hazard label: 3



Classification code: F1

Limited quantity: 5 L

Excepted quantity: E1

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 3295

**14.2. UN proper shipping name:** HYDROCARBONS, LIQUID, N.O.S.

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** III

Hazard label: 3



Special Provisions: 223

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-D

### Other applicable information (marine transport)

Staukategorie (stowage category)

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No information available.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: 79 %

Directive 2004/42/EC on VOC in paints and varnishes: 79 %

#### Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

#### Additional information

**Safety Data Sheet**

according to UK REACH Regulation

**beko Holzgleit**

Revision: 04.06.2025

Product code: 299 512/503

Page 10 of 10

Use restriction according to REACH annex XVII, no.: 3 , 40 ,not applicable (Specific end use(s) + Relevant identified uses)

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:  
Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten

**SECTION 16: Other information****Abbreviations and acronyms**

Flam. Liq. 3: Flammable liquids, hazard category 3  
Asp. Tox. 1: Aspiration hazard, hazard category 1  
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

| Classification     | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data    |
| STOT SE 3; H336    | Calculation method       |
| Asp. Tox. 1; H304  | Calculation method       |

**Relevant H and EUH statements (number and full text)**

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

**Identified uses**

| No | Short title    | LCS | SU | PC | PROC  | ERC       | AC | TF | Specification |
|----|----------------|-----|----|----|-------|-----------|----|----|---------------|
| 1  | Holgleitmittel | -   | -  | 15 | 7, 11 | 4, 8a, 9a | -  | -  | ES7           |

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*