

BYTUM PRIMER

UNIVERSAL PRIMER FOR MEMBRANES AND BITUMINOUS TAPES



HIGH PERFORMANCE

Prime coat before gluing bitumen-polymer membranes or applying bituminous liquid sheathing on cementitious and poorly cohesive structures. Applicable by spray, brush and roller.

VERSATILE

Excellent adhesion and penetration on all dry and even slightly wet cementitious surfaces. It blocks dustiness and porosity in concrete.



TECHNICAL DATA

Properties	standard	value	USC units
Colour (wet/dry)	-	brown/black	-
Time required for complete drying	-	30/60 min	-
Yield ⁽¹⁾	-	100/200 g/m ²	-
Density	ISO 2811-1	approx. 1 kg/L	-
Dry residue (130 °C)	ISO 3251	approx. 25%	-
Viscosity (outflow at 20 °C, Φ 4 mm)	ISO 2431	approx. 17 seconds	-
Storage temperature ⁽²⁾	-	> 5 °C	> 41 °F

⁽¹⁾ The data expressed may vary depending on the thickness of the product applied and the specific installation conditions: temperature, humidity, ventilation, absorptivity of the substrate.

⁽²⁾ Store the product in a dry, covered location in its original sealed container (frost sensitive).

CODES AND DIMENSIONS

CODE	content	content	
	[kg]	[lb]	
BYTP	10	22	1



REUSEABLE

Once the application is finished, it can be conveniently stored for later use by simply closing the bucket with its lid.

SAFE

Being water-based, it is particularly suitable for waterproofing work in inhabited areas, where the use of solvent-based products is not recommended.