

# RIDGE

## METAL ROLL

### FLEXIBLE VENTILATED ALUMINIUM UNDER-RIDGE

#### EXCELLENT ADHESION

The special 4 cm wide butyl tape ensures strong and immediate adhesion to various surfaces.

#### DURABILITY

The choice of metal material ensures excellent UV stability even in harsh climate zones.



### TECHNICAL DATA

Properties	value	USC units
Materials	aluminium, butyl	-
Butyl tape width	40 mm	1.57 in
Butyl tape adhesion property	> 19 N/cm	1.68 lbf/in
UV resistance	permanent	-
Application temperature	+5 / +25 °C	+41 / +77 °F
Temperature resistance	-30 / +80 °C	-22 / +176 °F
Storage temperature <sup>(1)</sup>	0 / +25 °C	+32 / +77 °F

<sup>(1)</sup> Keep the product in a dry, covered location.

Waste classification (2014/955/EU): 17 09 04.

### CODES AND DIMENSIONS

CODE	B	L	B	L	colour	RAL	
	[mm]	[m]	[in]	[ft]			
METRED400	400	5	15.8	16	brick red	8004	4
METBRO400	400	5	15.8	16	brown	8017	4
METANT400	400	5	15.8	16	anthracite	7021	4

### RECOMMENDATIONS FOR INSTALLATION

