

## BRUSH VENT

### RIGID UNDER-RIDGE WITH SIDE BRUSHES

#### FAST INSTALLATION

Thanks to its soft bristles, it adapts easily to the profile of the cover without the need for shaping.

#### PROTECTION

The bristles provide effective protection against the intrusion of water and foreign elements.




#### TECHNICAL DATA

Properties	value	USC units
Materials	PVC	-
Screen length	60 mm	2.36 in
Air passage	≥ 200 cm <sup>2</sup> /m	≥ 9.45 in <sup>2</sup> /ft
UV resistance	permanent	-
Temperature resistance	-20 / +80 °C	-4 / +176 °F

Waste classification (2014/955/EU): 17 02 03.

#### CODES AND DIMENSIONS

CODE	B	H	L	B	H	L	colour	RAL	
	[mm]	[mm]	[m]	[in]	[in]	[ft]			
BRUVENRED175	175	75	1	6.9	3.0	3	brick red	8004	20
BRUVENBRO175 <sup>(1)</sup>	175	75	1	6.9	3.0	3	brown	8019	20
BRUVENBLA175	175	75	1	6.9	3.0	3	black	9005	20

<sup>(1)</sup>Products available only upon order.

#### RECOMMENDATIONS FOR INSTALLATION

