

EMBEDDED ADJUSTABLE POST BASE

ADJUSTABLE

Height adjustable according to functional or aesthetic needs.

SIMPLE

Fastening is simplified by the absence of a base plate. Simply drill the hole in the concrete and embed the rod using a chemical anchor.

ECONOMICAL

It combines aesthetic performance and low cost, for small structures and non-structural applications.



CODES AND DIMENSIONS

CODE	H [mm] [in]	plate [mm] [in]	holes [n. x mm] [n. x in]	rod Ø x L [mm] [in]	pcs
R70100	40-250 1 9/16 - 10	100 x 100 x 8 4 x 4 x 0.31	4 x Ø11 4 x Ø0.43	20 x 350 0.79 x 13 3/4	1
R70140	45-350 1 9/16 - 13 3/4	140 x 140 x 8 5 1/2 x 5 1/2 x 0.31	4 x Ø11 4 x Ø0.43	24 x 450 0.95 x 17 3/4	1

SERVICE CLASS



MATERIAL



S235 carbon steel with special coating DAC COAT

GROUND CLEARANCE

adjustable from 40 to 350 mm



FIELD OF USE

Ground joints for columns, with the possibility of connecting the threaded rod directly to the concrete using a chemical anchor. Canopies, carports, pergolas

Suitable for columns in:

- solid timber softwood and hardwood
- Glulam, LVL

UK CONSTRUCTION PRODUCT EVALUATION

- UKTA-0836-22/6374.