

EXTRA-LONG ANCHOR WITH SCREW

- Plastic anchor for applications on semi-hollow and hollow brick
- Through fastening
- Complete with zinc plated steel screw with countersunk head
- Anti-rotational wings



CODES AND DIMENSIONS

CODE	d ₀	L _t		d _v x L _v		t _{fix}		h _{1,min}		bit	pcs
	[mm] [in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]		
NDS10100	10 0.40	100	4	7 x 105	0.28 x 4 1/8	25	0.98	85	3 3/8	TX40	25
NDS10120		120	4 3/4	7 x 125	0.28 x 4 15/16	45	1.77	85	3 3/8	TX40	25
NDS10140		140	5 1/2	7 x 145	0.28 x 5 11/16	65	2.56	85	3 3/8	TX40	25
NDS10160		160	6 1/4	7 x 165	0.28 x 6 1/2	85	3.35	85	3 3/8	TX40	25
NDS10200		200	8	7 x 205	0.28 x 8 1/16	125	4.92	85	3 3/8	TX40	25

EXTRA-LONG ANCHOR WITH IMPACT SCREW


- Plastic anchor with countersunk collar
- Through fastening
- Complete with zinc plated steel impact-screw with countersunk head



CODES AND DIMENSIONS

CODE	d ₀ [mm] <i>[in]</i>	L _t [mm] <i>[in]</i>	d _v x L _v [mm] <i>[in]</i>	t _{fix} [mm] <i>[in]</i>	h _{1,min} [mm] <i>[in]</i>	h _{ef} [mm] <i>[in]</i>	d _k [mm] <i>[in]</i>	bit	pcs
NDB640	6 0.24	40 1 9/16	3.8 x 45 0.15 x 1 3/4	10 0.39	30 1 3/16	27 1 1/16	10,0 0.39	PZ 2	200
NDB655		55 2 3/16	3.8 x 60 0.15 x 2 3/8	25 0.98	30 1 3/16	27 1 1/16	10,0 0.39	PZ 2	100
NDB667		67 2 5/8	3.8 x 72 0.15 x 2 13/16	37 1.46	30 1 3/16	27 1 1/16	10,0 0.39	PZ 2	100
NDB860	8 0.32	60 2 3/8	4.8 x 65 0.15 x 2 9/16	25 0.98	40 1 9/16	35 1 3/8	12,2 0.48	PZ 3	100
NDB875		75 2 15/16	4.8 x 80 0.15 x 3 1/8	40 1.57	40 1 9/16	35 1 3/8	12,2 0.48	PZ 3	100
NDB8100		100 4	4.8 x 105 0.15 x 4 1/8	65 2.56	40 1 9/16	35 1 3/8	12,2 0.48	PZ 3	50
NDB8120		120 4 3/4	4.8 x 125 0.15 x 4 15/16	85 3.35	40 1 9/16	35 1 3/8	12,2 0.48	PZ 3	50
NDB8135		135 5 5/16	4.8 x 140 0.15 x 5 1/2	100 3.94	40 1 9/16	35 1 3/8	12,2 0.48	PZ 3	50

GEOMETRY



- d₀ anchor diameter = hole diameter in the concrete support
- L_t anchor length
- d_v x L_v screw diameter x screw length
- t_{fix} maximum fastening thickness
- h₁ minimum hole depth
- h_{ef} effective anchoring depth
- d_k head diameter