

I SOLID

RIGID ANCHOR POINT FOR ROPE ACCESS WORK

DESIGNED FOR ROPE ACCESS WORK

The high-rigidity and high-strength support, combined with the multiple anchor plate, enables rope access work to be carried out comfortably and safely.

LIGHT

The aluminium alloy comprising the support facilitates handling and installation thanks to the lightweight components.

ADAPTABLE

Support height between 400 and 1000 mm adapts to different roofing thicknesses.

EN 17235:2024 KIT A	EN 795:2012 A	CEN/TS 18415:2013	BS 8810:2017 A1+A2+A3+A5	ANSI* Z359.18 -2017 A	AS 5532:2025
---------------------------	------------------	----------------------	--------------------------------	-----------------------------	-----------------

*The system has been developed and tested in accordance with the static, dynamic and residual strength requirements outlined in the relative ANSI standard.



MAXIMUM NUMBER
OF USERS



LOAD DIRECTION



TYPES OF
APPLICATION



MY
PROJECT
SAFETY



BIM



VIDEO



MANUALS



■ FIELDS OF APPLICATION





■ TECHNICAL DATA**

substructure	minimum thickness	fasteners	substructure	minimum thickness	fasteners
 CLT	160 mm	VGS (EVO) Ø13 HUS12 	 C20/25 ⁽¹⁾⁽²⁾ (uncracked)	140 mm	AB1 Ø12 
 S235	15 mm	bolt or rod M12 10.9 	⁽¹⁾ Applicable to EN 795 A and CEN/TS 16415 ⁽²⁾ Applicable up to SOLID800.		

SOLID / SOLIDRIG			
EN 795:2012 A	CEN/TS 16415:2013	EN 17235 KIT A	BS 8610:2017 A1+A2+A3+A5 AS 5532:2025
ANSI* Z359.18 - 2017 A			
maximum number of users	no.		

**The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a correct calculation report with minimum distances according to the standard requirements, the substructure must be checked by a qualified engineer before installation.

■ SOLID | CODES AND DIMENSIONS

CODE	description	material	d ₁ [mm]	B [mm]	L [mm]	H [mm]	pcs	
SOLID400	rigid support for rope access work	EN AW-6082-T6 	120	220	-	400	1	
SOLID600			120	220	-	600	1	
SOLID800			120	220	-	800	1	
SOLID1000			120	220	-	1000	1	
SOLIDPLATE	bottom plate for timber and concrete		-	550	595	-	1	
SOLIDRIG	multiple anchor plate for rope access work and safety disc	EN AW-6082-T6 black anodised 	310	-	-	-	1	
SOLIDPLATEFIX	fastening set comprising 8 nuts and 8 M12 8.8 bolts, for fastening SOLID to SOLIDPLATE	A2-70 stainless steel 	-	-	-	-	1	