

ROPES AND ACCESSORIES

ROPE105

STATIC THERMOTREATED POLYAMIDE ROPE WITH OUTER SHEATH Ø10.5 mm

- Static rope with a smooth sheath structure for improved abrasion resistance, easy use and good handling



CE

CODES AND DIMENSIONS

CODE	standard	L [m]	material	colour	weight [g/m]	strength [kN]	number of falls	elongation [%]	L [ft]	knottability
ROPE10560W	CE - EN 1891	60	PA	○	65,8	32	14	3,4	196' 10 1/4"	0,7
ROPE10570W	CE - EN 1891	70	PA	○	65,8	32	14	3,4	229' 7 7/8"	0,7
ROPE10580W	CE - EN 1891	80	PA	○	65,8	32	14	3,4	262' 5 5/8"	0,7
ROPE10590W	CE - EN 1891	90	PA	○	65,8	32	14	3,4	295' 3 1/4"	0,7
ROPE105100W	CE - EN 1891	100	PA	○	65,8	32	14	3,4	328' 1"	0,7
ROPE10560B	CE - EN 1891	60	PA	●	65,8	32	14	3,4	196' 10 1/4"	0,7
ROPE10570B	CE - EN 1891	70	PA	●	65,8	32	14	3,4	229' 7 7/8"	0,7
ROPE10580B	CE - EN 1891	80	PA	●	65,8	32	14	3,4	262' 5 5/8"	0,7
ROPE10590B	CE - EN 1891	90	PA	●	65,8	32	14	3,4	295' 3 1/4"	0,7
ROPE105100B	CE - EN 1891	100	PA	●	65,8	32	14	3,4	328' 1"	0,7
ROPE10560R	CE - EN 1891	60	PA	●	65,8	32	14	3,4	196' 10 1/4"	0,7
ROPE10570R	CE - EN 1891	70	PA	●	65,8	32	14	3,4	229' 7 7/8"	0,7
ROPE10580R	CE - EN 1891	80	PA	●	65,8	32	14	3,4	262' 5 5/8"	0,7
ROPE10590R	CE - EN 1891	90	PA	●	65,8	32	14	3,4	295' 3 1/4"	0,7
ROPE105100R	CE - EN 1891	100	PA	●	65,8	32	14	3,4	328' 1"	0,7

ROPE11

STATIC THERMOTREATED POLYAMIDE ROPE WITH OUTER SHEATH Ø11 mm

- Static rope with a smooth sheath structure for improved abrasion resistance, easy use and good handling



CE

CODES AND DIMENSIONS

CODE	standard	L [m]	material	colour	weight [g/m]	strength [kN]	number of falls	elongation [%]	L [ft]	knottability
ROPE1160W	CE - EN 1891	60	PA	○	77,9	37	24	3.1	196' 10 1/4"	0,7
ROPE1170W	CE - EN 1891	70	PA	○	77,9	37	24	3.1	229' 7 7/8"	0,7
ROPE1180W	CE - EN 1891	80	PA	○	77,9	37	24	3.1	262' 5 5/8"	0,7
ROPE1190W	CE - EN 1891	90	PA	○	77,9	37	24	3.1	295' 3 1/4"	0,7
ROPE11100W	CE - EN 1891	100	PA	○	77,9	37	24	3.1	328' 1"	0,7
ROPE1160B	CE - EN 1891	60	PA	●	77,9	37	24	3.1	196' 10 1/4"	0,7
ROPE1170B	CE - EN 1891	70	PA	●	77,9	37	24	3.1	229' 7 7/8"	0,7
ROPE1180B	CE - EN 1891	80	PA	●	77,9	37	24	3.1	262' 5 5/8"	0,7
ROPE1190B	CE - EN 1891	90	PA	●	77,9	37	24	3.1	295' 3 1/4"	0,7
ROPE11100B	CE - EN 1891	100	PA	●	77,9	37	24	3.1	328' 1"	0,7
ROPE1160R	CE - EN 1891	60	PA	●	77,9	37	24	3.1	196' 10 1/4"	0,7
ROPE1170R	CE - EN 1891	70	PA	●	77,9	37	24	3.1	229' 7 7/8"	0,7
ROPE1180R	CE - EN 1891	80	PA	●	77,9	37	24	3.1	262' 5 5/8"	0,7
ROPE1190R	CE - EN 1891	90	PA	●	77,9	37	24	3.1	295' 3 1/4"	0,7
ROPE11100R	CE - EN 1891	100	PA	●	77,9	37	24	3.1	328' 1"	0,7