

Specifications:

Spec. n.	Description	Unit of measurement	Price per unit	Total price
1	PERFORATED PLATE: Supply and installation, as provided for in the technical drawings of the project, of a metal perforated plate, with width B = ... mm, length L = ... mm and thickness S = 2 mm, PERFORATED PLATE produced and marketed by Rotho Blaas srl (www.rothoblaas.com), having the following characteristics: - class S 250 GD steel in accordance with norm DIN EN 10326:2004-09 with $f_{u,k} \geq 250 \text{ N/mm}^2$ - hot-dip galvanising for continuous immersion Z 275 (275 gr Z/m²) with minimum thickness 20 µm - CE marking for construction products in accordance with Directive 89/106/EEC, in accordance with EN 14245:2001 Furthermore, the plate is to be in possession of staggered holes with diameter Ø5 mm with inter-axis I = 20 mm. Installation must be carried out with Anker type improved adherence nails, diameter Ø4 mm and minimum length $L_{\min} = 40$ mm (or, alternatively, with special fully threaded screws Ø5 mm with minimum length $L_{\min} = 40$ mm, such as PF6035xx screws for perforated plates). Fastening can be carried out with total or partial nailing, in accordance with the technical drawings of the project. These indications are given in order to perform supply and installation to the best working standards. 	each	... €/each	... €