

Specifications:

Spec. n.	Description	Unit of measurement	Price per unit	Total price
1	NYLON DOWELS CE: Supply and installation, as provided for in the technical drawings of the project, of CE nylon dowels supplied with conical head screws, with dowel diameter $\varnothing = \dots$ mm, length L = ... mm, screw diameter $\varnothing = \dots$ mm and length L = ... mm, NYLON DOWELS CE WITH CONICAL HEAD SCREWS marked by Rotho Blaas srl (www.rothoblaas.com), having the following characteristics: - nylon dowels - conical head screws in galvanised or stainless steel - CE marking for construction products in accordance with Directive 89/106/CEE in compliance with ETAG 001 guidelines Furthermore, the dowels must be in possession of a special opening toward the end to improve anchoring, a reinforced edge for high resistance on cement and filled brick, wings for stopping turns, shaped surfaces with deep marking and an enlarged anti-penetration neck. Installation must be carried out in a properly pre-drilled pilot hole (10 mm hole deeper than the length of the piling with hole diameter = dowel diameter), screwing in the dowel with light hammering and inserting the screw by means of a screwdriver with suitable torsional coupling, avoiding use of "impact screwdrivers". These indications are given in order to perform supply and installation to the best working standards. 	each	... €/each	... €