

NAIL PLASTER

High-adhesiveness single-sided nail point sealant tape


Support film and closed-cell polyethylene (PP) foam profile with acrylic glue



5 mm version for more secure sealing
(NAILPLA550: colour grey)

PRACTICAL

With the help of LIZARD, installation is easy and fast, done directly on the ventilation battens



HERMETIC

The closed cell polyethylene structure ensures the opening created by the fixing systems is waterproof



CODES AND DIMENSIONS

code	ex code	s [mm]	B [mm]	L [m]	pcs/box	pcs/roll
NAILPLA350	D62202	3	50	30	10	-
NAILPLA35050	D62208	3	50 x 50	-	6	400
NAILPLA550	D63212	5	50	10	6	-

TECHNICAL SPECIFICATIONS

property	standard	value
Specific weight	ISO 845	approx. 30 kg/m ³
Tear strength MD/CD	ISO 1926	325 / 220 kPa
Elongation MD/CD	ISO 1926	125 / 115 %
Compression strength	ISO 3386/1	2 kPa at 10 % compression
	ISO 3386/1	3 kPa at 25 % compression
	ISO 3386/1	5 kPa at 50 % compression
Reaction to fire	DIN 4102 / EN 13501	class B2 / E
Water absorbancy	ISO 2896	< 2 % vol.
Thermal conductivity	-	0.04 W/mK (a +10 °C)
Temperature resistance	-	-30 / +80 °C
Application temperature	-	+5 / +40 °C
Storage temperature	-	+5 / +25 °C
Solvents	-	NO
VOC emissions	-	< 0.02 % (class A+)

NOTE: Store the product in a dry, covered location