

Specifications:

Spec. n.	Description	Unit of measurement	Price per unit	Total price
1	HEXAGONAL HEAD BOLTS WITH NUTS: Supply and installation, as provided for in the technical drawings of the project, of bolts, diameter $\varnothing = \dots$ mm and length $L = \dots$ mm, HEXAGONAL HEAD SCREWS, supplied with NUTS, produced and marketed by Rotho Blaas srl (www.rothoblaas.com), having the following characteristics: - class 8.8 steel with $f_{u,k} \geq 800 \text{ N/mm}^2$ - hot-dip galvanising for immersion for continuous immersion with minimum thickness $55 \mu\text{m}$ - partial threading under norm DIN 601 - CE marking for construction products in accordance with Directive 89/106/EEC, in accordance with EN 14592:2008 Furthermore, the bolts are to be in possession of a hexagonal, hot-dip galvanised DIN 934 nut, hexagonal head with indication of steel resistance class and trademark. Bolts must be installed with the addition of Din 440, DIN 9021 wood washers or DIN 1052 washers for large structures which are fully hot-dip galvanised in S235 steel. Installation is carried out by means of bolt insertion, in a properly pre-drilled pilot hole (with hole diameter = bolt diameter), by means of hand hammering of the head and later screwing of the nut. These indications are given in order to perform supply and installation to the best working standards. 	each	... €/each	... €