


TERRA BAND UV


Butyl adhesive tape, resistant to UV rays

Butyl compound coated with aluminium black film and separation layer




UV RAY STABLE

The special coating guarantee heat stability, resistance to ageing and to UV rays and durability of the material



BUTYL MIX

The special mix guarantees excellent adhesiveness and deformation capabilities, compensating for the natural movement of the wood



CODES AND DIMENSIONS

code	s [mm]	B [mm]	L [m]	pcs/box
TERRAUV75	0,8	75	10	1

TECHNICAL SPECIFICATIONS

property	standard	value
Reazione al fuoco	EN 13501	classe E
Resistenza allo strappo MD/CD	EN 12311-1	180 / 190 N/50 mm
Allungamento alla rottura MD/CD	EN 12311-1	15 / 20 %
Probe tack	ASTM D 2979	8 N
Adesività al distacco a 180°	ASTM D 1000	20 N/cm
Scivolamento verticale	ISO 7390	0 mm
Temperatura di applicazione	-	0 / +40 °C
Resistenza termica	-	-30 / +90 °C
Impermeabilità all'acqua	-	conforme
Fattore di resistenza al vapore (μ)	UNI EN 1931	2720000
Presenza solventi	-	NO
Emissioni VOC (COV)	-	0 % (classe A+)

NOTE: Store the product in a dry, covered location for no more than 12 months

COMPOSITION

separation layer: PE film

glue: adhesive butyl compound

support: aluminium black foil, UV stable