


TERRA BAND UV


Butyl adhesive tape, resistant to UV rays

Butyl compound coated with aluminium black film and separation layer




UV RAY STABLE

The special coating guarantee heat stability, resistance to ageing and to UV rays and durability of the material



BUTYL MIX

The special mix guarantees excellent adhesiveness and deformation capabilities, compensating for the natural movement of the wood



CODES AND DIMENSIONS

code	s [mm]	B [mm]	L [m]	pcs/box
TERRAUV75	0,8	75	10	1
TERRAUV100	0,8	100	10	1
TERRAUV200	0,8	200	10	1

TECHNICAL SPECIFICATIONS

property	standard	value
Reaction to fire	EN 13501	classe E
Tear strength MD/CD	EN 12311-1	180 / 190 N/50 mm
Elongation at break point MD/CD	EN 12311-1	15 / 20 %
Probe tack	ASTM D 2979	8 N
Detachment adhesion at 180°	ASTM D 1000	20 N/cm
Vertical sliding	ISO 7390	0 mm
Application temperature	-	0 / +40 °C
Temperature resistance	-	-30 / +90 °C
Watertightness	-	conforme
Water vapour resistance factor (μ)	UNI EN 1931	2720000
Solvents	-	NO
VOC emissions (COV)	-	0 % (classe A+)

NOTE: Store the product in a dry, covered location for no more than 12 months

COMPOSITION

separation layer: PE film

glue: adhesive butyl compound

support: aluminium black foil, UV stable