

TYP S50


PIED DE POTEAU HAUTEMENT RÉSISTANT

MATÉRIAU	acier au carbone
REVÊTEMENT	galvanisé à chaud (service class 3)
HAUTEUR	120 180 240 mm
RÉSISTANCE	compression supérieure à $R_k = 300$ kN
FIXATIONS	SKR, VIN-FIX PRO, HBS+ EVO




CODES ET DIMENSIONS


CODES	B x P x s [mm]	B ₁ x P ₁ x s ₁ [mm]	H [mm]	Ø x L [mm]	R _{1,k bois} ⁽¹⁾ [kN]	pcs.
TYP S501212	160 x 160 x 12	120 x 120 x 12	120	M20 x 120	274,0	1
TYP S501218	160 x 160 x 12	120 x 120 x 12	180	M20 x 120	274,0	1
TYP S501618	200 x 200 x 16	160 x 160 x 16	180	M24 x 150	344,0	1
TYP S501624	200 x 200 x 16	160 x 160 x 16	240	M24 x 150	344,0	1




MONTAGE TYP S50




01




02



03



04



05

B x P x s Dimensions plaque de base
B₁ x P₁ x s₁ Dimensions plaque supérieure
H Hauteur
Ø x L Diamètre et longueur de la tige

⁽¹⁾ R_{1,k bois} Valeur caractéristique de résistance à la compression côté bois. Le valeur de calcul s'obtient de la manière suivante :

$$R_d = \frac{R_{k \text{ bois}} \cdot k_{mod}}{\gamma_m}$$