

TRIPOD 3

MOBILE DEVICE WITH THREE FEET FOR LOWERING AND LIFTING

+ WINCH500 + RTCL10

EN 795/B CEN/TS 16415 EN 795/B CEN/TS 16415 EN 1496 EN 795/B CEN/TS 16415 EN 360



The TRIPOD 3 aluminium / steel safety support is part of the individual fall arrester. TRIPOD 3 has been tested according to EN 795 – TS 16415 as a class B provisional fixed point. The support must be used together with fall arresters.

- Material: **aluminium alloy / steel**
- Number of workers: **2**
- Maximum load: **500 kg**
- Weight: **16,1 kg**
- Transport dimensions: **130,4 x 28,1 x 31 cm**
- Height: **230,1 cm**
- Useful height: **181,4 cm**
- R_{max}: **1500 mm**

Despite its size and sturdiness, TRIPOD 3 is extremely light. It was designed for quick assembly and safe use. It can be used to carry loads or to rescue people. Provided with an anchor point (integrated in the top of the device).

CODES AND DIMENSIONS

CODE	material	pcs.
TRI3	aluminium alloy / steel	1

COMPLEMENTARY PRODUCTS

CODE	description	pcs.
TRICABLE12	12 m Ø5 mm cable	1
WINCH500	winch for 500 kg load	1
RTCL10	retractable 10 m	1



TECHNICAL DATA

1. Built-in sheave for sliding the work cable
2. Side attachment point
3. Leg (3 pieces)
4. Self adjusting support with rubber bushing and non-slip teeth
5. Lynchpin for regulation of the tripod leg
6. Retractable 10 m

