


KKA AISI410

WOOD SELF-PERFORATING | WPC-ALUMINIUM

MATERIAL	martensitic stainless steel AISI410
HEAD	concealed cylindrical
SPECIAL	self-perforating tip for aluminium
DIAMETER	from 4,0 to 5,0 mm
LENGTH	from 20 to 50 mm




FASTENING THICKNESS



CODES AND DIMENSIONS

CODES	TX	d ₁ x L [mm]	d _k [mm]	b [mm]	A [mm]	s ₂ [mm]	pcs.
KKA420	20	4 x 20	6,3	15	5	1÷2	200
KKA540	25	5 x 40	6,8	22	18	1÷3	100
KKA550	25	5 x 50	6,8	27	23	1÷3	100



d₁ x L
d_k
b
A

Nominal diameter and length of the screw
Head diameter
Thread
Fastening thickness

TX
s₂

Bit
Thickness, aluminium plate


■ KKA N

ALUMINIUM SELF-PERFORATING

MATERIAL	carbon steel with corrosion-resistant organic coating
HEAD	concealed cylindrical
SPECIAL	self-perforating tip for aluminium and fine thread
DIAMETER	4,0 mm
LENGTH	30 40 mm
COLOUR	black




FASTENING THICKNESS



CODES AND DIMENSIONS

CODES	TX	$d_1 \times L$ [mm]	d_k [mm]	b [mm]	A [mm]	pcs.
KKAN430	20	4 x 30	6,3	25	5	200
KKAN440	20	4 x 40	6,3	35	5	200



$d_1 \times L$ Nominal diameter and length of the screw
 d_k Head diameter
b Thread
A Fastening thickness

TX
 s_1 Bit
 s_2 Thickness, steel plate S235 / St37
 Thickness, aluminium plate